

Package: RAQSAPI (via r-universe)

October 2, 2026

Type Package

Version 2.0.6

Title A Simple Interface to the US EPA Air Quality System Data Mart API

Description Retrieve air monitoring data and associated metadata from the US Environmental Protection Agency's Air Quality System service using functions. See https://aqs.epa.gov/aqsweb/documents/data_api.html for details about the US EPA Data Mart API [doi:10.32614/CRAN.package.RAQSAPI](https://doi.org/10.32614/CRAN.package.RAQSAPI).

Encoding UTF-8

URL <https://usepa.github.io/RAQSAPI/>,
<https://github.com/USEPA/RAQSAPI/>,
https://aqs.epa.gov/aqsweb/documents/data_api.html

BugReports <https://github.com/USEPA/RAQSAPI/issues>

Depends R (>= 4.5.0)

Imports dplyr, glue, httr2, lifecycle, lubridate, methods, magrittr, purrr, rlang, stringr, tibble, tidyselect

Suggests cli, covr, devtools, goodpractice, httptest2, keyring, knitr, pak, rmarkdown, roxygen2, spelling, testthat (>= 3.0.0), usethis

SystemRequirements package manual and Vignettes require pandoc (>= 1.14) (<http://pandoc.org>)

VignetteBuilder knitr

BuildVignettes true

ByteCompile true

License MIT + file LICENSE

License_is_FOSS yes

NeedsCompilation no

License_restricts_use no

Language en-US

Classification/ACM-2012 H.3.5 Information Systems—Web-based services,
J.2 Applied Computing—Earth and atmospheric sciences, G.3
Mathematics of Computing—Probability and statistics

Collate 'RAQSAPI-package.R' 'utils-pipe.R'
'AQS_DATAMART_APIv2-S3-class.R' 'AQSAPI_helperfunctions.R'
'bysite.R' 'bycounty.R' 'bystate.R' 'byma.R' 'bypqao.R'
'bycbas.R' 'bybox.R' 'RAQSAPIlistfunctions.R'
'setupfunctions.R' 'zzz.R'

Copyright United States Environmental Protection Agency

RdMacros lifecycle

Roxygen list(markdown = TRUE)

X-schema.org-keywords United State Environmental Protection Agency,
Environmental-data-retrieval, Air-Quality-System, AQS-DataMart,
Air-monitoring, Environmental-monitoring

Config/testthat/edition 3

Config/testthat/load-all list(export_all = FALSE, helpers = FALSE)

Config/testthat/parallel false

Config/build/clean-inst-doc true

Config/roxygen2/version 8.1.0

Config/roxygen2/markdown TRUE

Config/pak/sysreqs libicu-dev libssl-dev

Repository <https://usepa.r-universe.dev>

Date/Publication 2026-10-02 20:54:01 UTC

RemoteUrl <https://github.com/usepa/raqsapi>

RemoteRef HEAD

RemoteSha 0f9f9fa2e483b17d5a8b0fe67d5e8dc834a973ed

Contents

aqс_annualsummary_by_box	4
aqс_annualsummary_by_cbsa	6
aqс_annualsummary_by_county	8
aqс_annualsummary_by_site	10
aqс_annualsummary_by_state	12
aqс_cbsas	14
aqс_classes	15
aqс_counties_by_state	15
aqс_credentials	16
aqс_dailysummary_by_box	17
aqс_dailysummary_by_cbsa	19
aqс_dailysummary_by_county	21

aqs_dailysummary_by_site	23
aqs_dailysummary_by_state	25
aqs_fields_by_service	26
aqs_isavailable	27
aqs_knownissues	28
aqs_mas	28
aqs_monitors_by_box	29
aqs_monitors_by_cbsa	30
aqs_monitors_by_county	32
aqs_monitors_by_site	33
aqs_monitors_by_state	35
aqs_parameters_by_class	36
aqs_pqaos	37
aqs_qa_annualperformanceeval_by_county	37
aqs_qa_annualperformanceeval_by_MA	39
aqs_qa_annualperformanceeval_by_pqao	41
aqs_qa_annualperformanceeval_by_site	42
aqs_qa_annualperformanceeval_by_state	44
aqs_qa_annualperformanceevaltransaction_by_county	46
aqs_qa_annualperformanceevaltransaction_by_MA	47
aqs_qa_annualperformanceevaltransaction_by_pqao	49
aqs_qa_annualperformanceevaltransaction_by_site	51
aqs_qa_annualperformanceevaltransaction_by_state	52
aqs_qa_blanks_by_county	54
aqs_qa_blanks_by_MA	56
aqs_qa_blanks_by_pqao	57
aqs_qa_blanks_by_site	59
aqs_qa_blanks_by_state	60
aqs_qa_collocated_assessments_by_county	62
aqs_qa_collocated_assessments_by_MA	64
aqs_qa_collocated_assessments_by_pqao	65
aqs_qa_collocated_assessments_by_site	67
aqs_qa_collocated_assessments_by_state	69
aqs_qa_flowrateaudit_by_county	70
aqs_qa_flowrateaudit_by_MA	72
aqs_qa_flowrateaudit_by_pqao	73
aqs_qa_flowrateaudit_by_site	75
aqs_qa_flowrateaudit_by_state	77
aqs_qa_flowrateverification_by_county	78
aqs_qa_flowrateverification_by_MA	80
aqs_qa_flowrateverification_by_pqao	82
aqs_qa_flowrateverification_by_site	83
aqs_qa_flowrateverification_by_state	85
aqs_qa_one_point_qc_by_county	87
aqs_qa_one_point_qc_by_MA	88
aqs_qa_one_point_qc_by_pqao	90
aqs_qa_one_point_qc_by_site	91
aqs_qa_one_point_qc_by_state	93

aqs_qa_pep_audit_by_county	95
aqs_qa_pep_audit_by_MA	96
aqs_qa_pep_audit_by_pqao	98
aqs_qa_pep_audit_by_site	99
aqs_qa_pep_audit_by_state	101
aqs_quarterlysummary_by_box	103
aqs_quarterlysummary_by_cbsa	105
aqs_quarterlysummary_by_county	107
aqs_quarterlysummary_by_site	109
aqs_quarterlysummary_by_state	111
aqs_removeheader	113
aqs_revisionhistory	113
aqs_sampledata_by_box	114
aqs_sampledata_by_cbsa	116
aqs_sampledata_by_county	118
aqs_sampledata_by_site	120
aqs_sampledata_by_state	123
aqs_sampledurations	125
aqs_sign_up	126
aqs_sites_by_county	126
aqs_states	127
aqs_transactionsample_by_county	128
aqs_transactionsample_by_MA	130
aqs_transactionsample_by_site	131
aqs_transactionsample_by_state	133

Index 136

aqs_annualsummary_by_box
aqs_annualsummary_by_box

Description

[Stable] Returns multiple years of data where annual data is aggregated at the bounding box level. Returned is an annual summary within the input parameter, latitude/longitude bounding box provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
```

```

    minlon,
    maxlon,
    cbdate = lubridate::NA_Date_,
    cedate = lubridate::NA_Date_,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object that represents the minimum latitude of a geographic box. Decimal latitude with north being positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north being positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east being positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east being positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

A tibble or an AQS_DataMart_APIv2 S3 object that containing annual summary data for the box (area) requested. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annual summary data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5)$ seconds).

See Also

Other Aggregate _by_box functions: [aqs_monitors_by_box\(\)](#), [aqs_sampledata_by_box\(\)](#)

Examples

```
# Returns a tibble containing ozone annual summaries
#   in the vicinity of central Alabama for the first two days
#   of May, 2015
## Not run: aqs_annualsummary_by_box(parameter = '44201',
                                     bdate = as.Date('20150501',
                                                       format = '%Y%m%d'),
                                     edate = as.Date('20170502',
                                                       format = '%Y%m%d'),
                                     minlat = '33.3',
                                     maxlat = '33.6',
                                     minlon = '-87.0',
                                     maxlon = '-86.7'
                                     )

## End(Not run)
```

aqs_annualsummary_by_cbsa

aqs_annualsummary_by_cbsa

Description

[Stable] Returns multiple years of data where annual data is aggregated at the Core Based Statistical Area (CBSA) level. Returned is an annual summary matching the input parameter, and cbsa_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqsum_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros). Use aqsum_cbsas() for a list of all CBSA codes and names available,
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

A tibble or an AQS_DataMart_APIv2 S3 object that containing annual summary data for the cbsa_code requested. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each

calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_cbsa functions: [aq_s_dailysummary_by_cbsa\(\)](#), [aq_s_monitors_by_cbsa\(\)](#), [aq_s_sampledata_by_cbsa\(\)](#)

Examples

```
# Returns a tibble of annual summary $NO_{2}$
# data the for Charlotte-Concord-Gastonia, NC cbsa on
# Janurary 01, 2017
## Not run: aqs_annualsummary_by_cbsa(parameter = '42602',
                                     bdate = as.Date('20170101',
                                                       format = '%Y%m%d'
                                                     ),
                                     edate = as.Date('20170101',
                                                       format = '%Y%m%d'
                                                     ),
                                     cbsa_code = '16740'
                                     )

## End(Not run)
```

aq_s_annualsummary_by_county

aq_s_annualsummary_by_county

Description

[Stable] Returns multiple years of data where annual data is aggregated at the county level. Returned is an annual summary matching the input parameter, stateFIPS, and county_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = lubridate::NA_Date_,
```

```

    cdate = lubridate::NA_Date_,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsum_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqsum_counties_by_state() for the list of available county codes in each state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cdater	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cdate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

A tibble or an AQS_DataMart_APIv2 S3 object that containing annual summary data for the countycode and stateFIPS requested. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_county functions: [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_annualperformanceeval_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_quarterlysummary_by_county\(\)](#), [aq_s_quarterlysummary_by_site\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns an aqs S3 object with annual summary FRM/FEM
#   PM2.5 data for Wake County, NC between January
#   and February 2016
## Not run: aqs_annualsummary_by_county(parameter = '88101',
                                         bdate = as.Date('20160101',
                                                           format = '%Y%m%d'),
                                         edate = as.Date('20180228',
                                                           format = '%Y%m%d'),
                                         stateFIPS = '37',
                                         countycode = '183'
                                         )

## End(Not run)
```

aq_s_annualsummary_by_site

aq_s_annualsummary_by_site

Description

[Stable] Returns multiple years of data where annual data is aggregated at the site level. Returned is an annual summary matching the input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing annual summary data for the sitenum, countycode and stateFIPS requested. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_annualperformanceeval_by_site\(\)](#), [aq_s_qa_annualperformanceevaltransaction_by_county\(\)](#), [aq_s_qa_annualperformanceevaltransaction_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessm](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```
# Returns a tibble of annual summary ozone
# data for the Millbrook School site (\#0014) in Wake County,
# NC for 2017 (Note, for annual data, only the
# year portion of the bdate and edate are used and only whole
# years of data are returned. For example, bdate = 2017-12-31 and
# edate = 2018-01-01 will return full data for 2017 and 2018 )
## Not run:
aqs_annualsummary_by_site(parameter = '44201',
                           bdate = as.Date('20170618',
                                             format='%Y%m%d'),
                           edate = as.Date('20190618',
                                             format='%Y%m%d'),
                           stateFIPS = '37',
                           countycode = '183',
                           sitenum = '0014'
                           )

## End(Not run)
```

aq_s_annualsummary_by_state

aq_s_annualsummary_by_state

Description

[Stable] Returns multiple years of data where annual data is aggregated at the state level. Returned is an annual summary matching the input parameter and stateFIPS provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = lubridate::NA_Date_,
```

```

    cdate = lubridate::NA_Date_,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use <code>aqsum_states()</code> for the list of available FIPS codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cdater	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cdate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

A tibble or an AQS_DataMart_APIv2 S3 object that containing annual summary data for the state-FIPS requested. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqc_dailysummary_by_state\(\)](#), [aqc_monitors_by_state\(\)](#), [aqc_qa_blanks_by_state\(\)](#), [aqc_qa_collocated_assessments_by_state\(\)](#), [aqc_qa_flowrateaudit_by_state\(\)](#), [aqc_qa_flowrateverification_by_state\(\)](#), [aqc_qa_one_point_qc_by_state\(\)](#), [aqc_qa_pep_audit_by_state\(\)](#), [aqc_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of all benzene annualy
# summaries from North Carolina collected for 1995
## Not run: aqc_annualsummary_by_state(parameter = '45201',
                                     bdate = as.Date('19950515',
                                     format='%Y%m%d'
                                     ),
                                     edate = as.Date('19950515',
                                     format = '%Y%m%d'
                                     ),
                                     stateFIPS = '37'
                                     )

## End(Not run)
```

aqc_cbsas	<i>aqc_cbsas</i>
-----------	------------------

Description

[Stable] Returns a table of all Core Based Statistical Areas (cbsa) and their associated cbsa_codes. for constructing other requests.

Usage

```
aqc_cbsas(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of all Core Based Statistical Areas (cbsa) and their cbsa_codes for constructing other requests.

Examples

```
# Returns a tibble of Core Based Statistical Areas (cbsas)
# and their respective cbsa codes
## Not run: aqs_cbsas()
```

aqs_classes

aqs_classes

Description

[Stable] Returns a table of Parameter classes (groups of parameters, i.e. 'criteria' or 'all'). The information from this function can be used as input to other API calls.

Usage

```
aqs_classes(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of Parameter classes (groups of parameters, i.e. 'criteria' or 'all').

Examples

```
# Returns a tibble of parameter classes (groups of parameters, i.e.
# 'criteria' or 'all')
## Not run: aqs_classes()
```

aqs_counties_by_state *aqs_counties_by_state*

Description

[Stable] Returns a table of all counties in within the stateFIPS provided.

Usage

```
aqs_counties_by_state(stateFIPS, return_header = FALSE)
```

Arguments

- stateFIPS a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use [aq_s_states\(\)](#) for the list of available FIPS codes.
- return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of all counties in the requested state.

Examples

```
# Returns a tibble all the counties
#   in North Carolina the county FIPS codes (county codes) for
#   each.
## Not run: aqs_counties_by_state(stateFIPS = '37')
```

aq _s _credentials	<i>aq_s_credentials</i>
------------------------------	-----------------------------------

Description

[Stable] Sets the user credentials for the AQS API. This function needs to be called once and only once every time this library is re-loaded. Users must have a valid username and key which can be obtained through the use of the [aq_s_sign_up](#) function, Use [aq_s_sign_up\(\)](#) to sign up for AQS datamart credentials.

Usage

```
aqs_credentials(username = NA_character_, key = NA_character_)
```

Arguments

- username a R character object which represents the email account that will be used to connect to the AQS API.
- key the key used in conjunction with the username given to connect to AQS Data Mart.

Value

NULL (invisible) This functions is called for its side effect and does not return meaningful data.

Examples

```
#to authenticate an existing user the email address
# 'John.Doe@myemail.com' and key = 'MyKey'
# after calling this function please follow the instructions that are sent
# in the verification e-mail before proceeding.
## Not run: aqs_credentials(username = 'John.Doe@myemail.com',
                           key = 'MyKey')

## End(Not run)
```

aqs_dailysummary_by_box

aqs_dailysummary_by_box

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object containing daily summary data bounded within a latitude/longitude bounding box

Usage

```
aqs_dailysummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object that represents the minimum latitude of a geographic box. Decimal latitude with north being positive. Only data north of this latitude will be returned.


```

    edate = as.Date('20160502',
                    format = '%Y%m%d'
                    ),
    mqinlat = '33.3',
    maxlat = '33.6',
    minlon = '-87.0',
    maxlon = '-86.7'
  )

## End(Not run)

```

```
aqsummary_by_cbsa
```

```
aqsummary_by_cbsa
```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object containing daily summary data aggregated by cbsa (Core Based Statistical Area) code.

Usage

```

aqsummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros). Use aqsummary_by_cbsa() for a list of all CBSA codes and names available,
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that contains daily summary statistics for the given parameter for a single cbsa_code. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_cbsa functions: [aqsanualsummary_by_cbsa\(\)](#), [aqsmotors_by_cbsa\(\)](#), [aqssampledta_by_cbsa\(\)](#)

Examples

```
# Returns a tibble of $NO_{2}$ daily summary
# data the for Charlotte-Concord-Gastonia, NC cbsa on
# Janurary 01, 2017
## Not run: aqsdailysummary_by_cbsa(parameter = '42602',
                                   bdate = as.Date('20170101',
                                                    format = '%Y%m%d'
                                                    ),
                                   edate = as.Date('20190101',
                                                    format = '%Y%m%d'
                                                    ),
                                   cbsa_code = '16740'
                                   )

## End(Not run)
```

```
aqs_dailysummary_by_county
      aqs_dailysummary_by_county
```

Description

[Stable] Returns multiple years of data where daily data is aggregated at the site level. Returned is a daily summary matching the input parameter, stateFIPS and county_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc.

Usage

```
aqs_dailysummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

```
aqs_dailysummary_by_site
      aqs_dailysummary_by_site
```

Description

[Stable] Returns multiple years of data where dailysummary data is aggregated at the site level. Returned is a daily summary matching the input parameter stateFIPS, countycode, and sitenum provided for bdate - edate time frame. Data is aggregated at the state level. Variables returned include mean value, maxima, percentiles, and etc.

Usage

```
aqs_dailysummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that contains daily summary statistics for the given parameter for a single site. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aqsdailysummary_by_site\(\)](#), [aqsmotors_by_site\(\)](#), [aqsqannualperformanceeval_by_site\(\)](#), [aqsqannualperformanceevaltransaction_by_county\(\)](#), [aqsqannualperformanceevaltransaction_by_site\(\)](#), [aqsqblanks_by_site\(\)](#), [aqsqcollocated_assessm](#), [aqsqflowrateaudit_by_site\(\)](#), [aqsqflowrateverification_by_site\(\)](#), [aqsqone_point_qc_by_site\(\)](#), [aqsqpep_audit_by_site\(\)](#), [aqssampledataby_site\(\)](#), [aqstransactionssample_by_site\(\)](#)

Examples

```
#Returns a tibble of daily summary ozone
# data for the Millbrook School site (\#0014) in Wake County,
# NC for June 18, 2017.
## Not run:
aqsdailysummary_by_site(parameter = '44201',
                        bdate = as.Date('20160618',
                                         format = '%Y%m%d'),
                        edate = as.Date('20190618',
                                         format = '%Y%m%d'),
                        stateFIPS = '37',
                        countycode = '183',
                        sitenum = '0014'
                        )

## End(Not run)
```

```
aqs_dailysummary_by_state
      aqs_dailysummary_by_state
```

Description

[Stable] Returns multiple years of data where daily data is aggregated at the state level. Returned is a daily summary matching the input parameter and stateFIPS provided for bdate - edate time frame. Data is aggregated at the state level. Variables returned include mean value, maxima, percentiles, and etc.

Usage

```
aqs_dailysummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that contains daily summary statistics for the given parameter for a single stateFIPS. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqс_annualsummary_by_state\(\)](#), [aqс_monitors_by_state\(\)](#), [aqс_qa_blanks_by_state\(\)](#), [aqс_qa_collocated_assessments_by_state\(\)](#), [aqс_qa_flowrateaudit_by_state\(\)](#), [aqс_qa_flowrateverification_by_state\(\)](#), [aqс_qa_one_point_qc_by_state\(\)](#), [aqс_qa_pep_audit_by_state\(\)](#), [aqс_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of all benzene daily
# summaries from North Carolina collected on May 15th, 1995
## Not run: aqs_dailysummary_by_state(parameter = '45201',
                                     bdate = as.Date('19950515',
                                     format='%Y%m%d'
                                     ),
                                     edate = as.Date('19970515',
                                     format = '%Y%m%d'
                                     ),
                                     stateFIPS = '37'
                                     )

## End(Not run)
```

aqс_fields_by_service *aqс_fieldsbyservice*

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object with the list and definitions of fields in the service requested.

Usage

```
aqsis_fields_by_service(service, return_header = FALSE)
```

Arguments

service a string which represents the services provided by the AQS API. For a list of available services, refer to https://aqs.epa.gov/aqsweb/documents/data_api.html#services

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object with containing the list and definitions of fields requested service

Examples

```
# Returns a tibble containing a list and definitions
#   of fields in the Sample Data service
## Not run: aqsis_fieldsby_service(service = 'sampleData')
```

aqsis_isavailable	<i>aqsis_isavailable</i>
-------------------	--------------------------

Description

[Stable] returns a tibble that details the status of the AQS Data Mart API.

Usage

```
aqsis_isavailable()
```

Value

a tibble that details the status of the AQS Data Mart API.

Examples

```
# Check if the AQS API is up, running and accepting requests.
## Not run: aqsis_isAvailable()
```

aqs_knownissues	<i>aqs_knownissues</i>
-----------------	------------------------

Description

[Stable] Returns a table of any known issues with system functionality or the data. These are usually issues that have been identified internally and will require some time to correct in Data Mart or the API. This function implements a direct API call to Data Mart and returns data directly from the API. Issues returned via this function do not include any issues from the RAQSAPI R package.

Usage

```
aqs_knownissues(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that contains information involving known issues with the Data Mart API.

Examples

```
# Retrieve a tibble of known issues directly from the AQS data mart API
## Not run: aqs_knownissues()
```

aqs_mas	<i>aqs_mas</i>
---------	----------------

Description

[Stable] Returns a table of monitoring agencies (MA).

Usage

```
aqs_mas(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of monitoring agencies and their associated agency code.

Examples

```
# Returns a tibble or an AQS_DataMart_APIv2 S3 object
# of monitoring agencies and their respective
# monitoring agency codes.
## Not run: aqs_mas()
```

aq _s _monitors_by_box	<i>aq_s_monitors_by_box</i>
----------------------------------	---------------------------------------

Description

[Stable] Returns a table of monitors and related metadata sites with the provided parameter, aggregated by latitude/longitude bounding box (*_by_box*) for bdate - edate time frame.

Usage

```
aqs_monitors_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object that represents the minimum latitude of a geographic box. Decimal latitude with north being positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north being positive. Only data south of this latitude will be returned.

minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of monitors from a latitude/longitude bounding box (_by_box).

Note

All monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate _by_box functions: [aq_s_annualsummary_by_box\(\)](#), [aq_s_sampledata_by_box\(\)](#)

Examples

```
# Returns a tibble of all ozone
# monitors in the vicinity of central Alabama that operated in
# 1995
## Not run: aqs_monitors_by_box(parameter='44201',
                                bdate=as.Date('19950101',
                                                format='%Y%m%d'),
                                edate=as.Date('19951231',
                                                format='%Y%m%d'),
                                minlat='33.3',
                                maxlat='33.6',
                                minlon='-87.0',
                                maxlon='-86.7'
                                )

## End(Not run)
```

aq_s_monitors_by_cbsa *aq_s_monitors_by_cbsa*

Description

[Stable] Returns a table of monitors at all sites with the provided parameter, aggregated by Core Based Statistical Area (CBSA) for bdate - edate time frame.

Usage

```
aqs_monitors_by_cbsa(parameter, bdate, edate, cbsa_code, return_header = FALSE)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros). Use aq_s_cbsas() for a list of all CBSA codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that is the return value from the AQS API. A AQS_DataMart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

All monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate _by_cbsa functions: [aq_s_annualsummary_by_cbsa\(\)](#), [aq_s_dailysummary_by_cbsa\(\)](#), [aq_s_sampledata_by_cbsa\(\)](#)

Examples

```
# returns a tibble of $NO_{2}$ monitors
# for Charlotte-Concord-Gastonia, NC cbsa that were operating
# on January 01, 2017
## Not run: aqs_monitors_by_cbsa(parameter='42602',
                                bdate=as.Date('20170101',
                                                format='%Y%m%d'),
                                edate=as.Date('20170101',
                                                format='%Y%m%d'),
                                cbsa_code='16740'
                                )

## End(Not run)
```

```
aqs_monitors_by_county
      aqs_monitors_by_county
```

Description

[Stable] Returns a table of monitors and related metadata at sites with the provided parameter, stateFIPS and county_code for bdate - edate time frame.

Usage

```
aqs_monitors_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aq_s_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of monitors from a selected county

Note

All monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate _by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_qa_annualperformanceeval_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_quarterlysummary_by_county\(\)](#), [aq_s_quarterlysummary_by_site\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns an aqs_v2 S3 object containing all S02 monitors in
# Hawaii County, HI that were operating between May 01-02, 2015.
## Not run: aqs_monitors_by_county(parameter='42401',
                                bdate=as.Date('20150501', format='%Y%m%d'),
                                edate=as.Date('20150502', format='%Y%m%d'),
                                stateFIPS='15',
                                countycode='001'
                                )

## End(Not run)
```

aq _s _monitors_by_site	<i>aq_s_monitors_by_site</i>
-----------------------------------	--

Description

[Stable] Returns a table of monitors and related metadata at sites with the provided parameter, stateFIPS, county_code, and sitenum for bdate - edate time frame.

Usage

```
aqs_monitors_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

- | | |
|-----------|---|
| parameter | a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested. |
| bdate | a R date object which represents the begin date of the data selection. Only data on or after this date will be returned. |

edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of monitors from a selected stateFIPS, county, and sitenum combination.

Note

All monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate_by_site functions: [aqs_annualsummary_by_site\(\)](#), [aqs_dailysummary_by_site\(\)](#), [aqs_qa_annualperformanceeval_by_site\(\)](#), [aqs_qa_annualperformanceevaltransaction_by_county\(\)](#), [aqs_qa_annualperformanceevaltransaction_by_site\(\)](#), [aqs_qa_blanks_by_site\(\)](#), [aqs_qa_collocated_assessm](#), [aqs_qa_flowrateaudit_by_site\(\)](#), [aqs_qa_flowrateverification_by_site\(\)](#), [aqs_qa_one_point_qc_by_site\(\)](#), [aqs_qa_pep_audit_by_site\(\)](#), [aqs_sampledata_by_site\(\)](#), [aqs_transactionsample_by_site\(\)](#)

Examples

```
#Returns a tibble of the SO2 monitors at Hawaii
# Volcanoes NP site (\#0007) in Hawaii County, HI that were operating
# between May 1 , 2015-2019. (Note, all monitors that operated between the
# bdate and edate will be returned).
## Not run:
aqs_monitors_by_site(parameter = '42401',
                      bdate = as.Date('20150501',
                                      format='%Y%m%d'),
                      edate = as.Date('20190501',
                                      format='%Y%m%d'),
                      stateFIPS = '15',
                      countycode = '001',
                      sitenum = '0007'
                      )
```

```
## End(Not run)
```

```
aqs_monitors_by_state  aqs_monitors_by_state
```

Description

[Stable] Returns a table of monitors and related metadata at sites with the provided parameter, and stateFIPS for bdate - edate time frame.

Usage

```
aqs_monitors_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of monitors from the selected state

Note

All monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate_by_state functions: [aqs_annualsummary_by_state\(\)](#), [aqs_dailysummary_by_state\(\)](#), [aqs_qa_blanks_by_state\(\)](#), [aqs_qa_collocated_assessments_by_state\(\)](#), [aqs_qa_flowrateaudit_by_state\(\)](#), [aqs_qa_flowrateverification_by_state\(\)](#), [aqs_qa_one_point_qc_by_state\(\)](#), [aqs_qa_pep_audit_by_state\(\)](#), [aqs_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of SO2 monitors in Hawaii
#   that were operating on May 01, 2017
## Not run: aqs_monitors_by_state(parameter='88101',
                                bdate=as.Date('20170101',
                                                format='%Y%m%d'),
                                edate=as.Date('20171231',
                                                format='%Y%m%d'),
                                stateFIPS='01'
                                )

## End(Not run)
```

aqs_parameters_by_class
<i>aqs_parameters_by_class</i>

Description

[Stable] Returns parameters associated with the input class.

Usage

```
aqs_parameters_by_class(class, return_header = FALSE)
```

Arguments

- class a R character object that represents the class requested, Use [aqs_classes\(\)](#) for retrieving available classes. The class R character object must be a valid class as returned from [aqs_classes\(\)](#). The class must be an exact match to what is returned from [aqs_classes\(\)](#) (case sensitive).
- return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing the parameters associated with the class requested. NULL is returned for classes not found.

Examples

```
# Returns a tibble of AQS parameters in the criteria class
## Not run: aqs_parameters_by_class(class = 'CRITERIA')
```

aq _s _pqaos	<i>aq_s_pqaos</i>
------------------------	-----------------------------

Description

[Stable] Returns a table of primary quality assurance organizations (pqaos).

Usage

```
aqs_pqaos(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of pqaos and their associated pqao code.

Examples

```
# Returns a tibble of primary quality assurance
# organizations (pqaos)
## Not run: aqs_pqaos()
```

aq _s _qa_annualperformanceeval_by_county	<i>aq_s_qa_annualperformanceeval_by_county</i>
---	--

Description

[Stable] Returns quality assurance performance evaluation data - aggregated by county for a parameter code aggregated by matching input parameter, countycode and stateFIPS provided for bdate - edate time frame.

Usage

```
aqs_qa_annualperformanceeval_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_county` functions: `aqs_annualsummary_by_county()`, `aqs_dailysummary_by_county()`, `aqs_monitors_by_county()`, `aqs_qa_blanks_by_county()`, `aqs_qa_collocated_assessments_by_county()`, `aqs_qa_flowrateaudit_by_county()`, `aqs_qa_flowrateverification_by_county()`, `aqs_qa_one_point_qc_by_county()`, `aqs_qa_pep_audit_by_county()`, `aqs_quarterlysummary_by_county()`, `aqs_quarterlysummary_by_site()`, `aqs_sampledata_by_county()`, `aqs_transactionsample_by_county()`

Examples

```
# Returns a tibble containing annual performance evaluation data
# for ozone in Baldwin County, AL for 2017.
## Not run: aqs_qa_annualperformanceeval_by_county(parameter = '44201',
                                                    bdate = as.Date('20170101',
                                                    format = '%Y%m%d'),
                                                    edate = as.Date('20171231',
                                                    format = '%Y%m%d'),
                                                    stateFIPS = '01',
                                                    countycode = '003'
                                                    )

## End(Not run)
```

```
aqs_qa_annualperformanceeval_by_MA
```

```
    aqs_qa_annualperformanceeval_by_MA
```

Description

[Stable] Returns quality assurance performance evaluation data - aggregated by Monitoring agency (MA) for a parameter code aggregated by matching input parameter and MA_code for the time frame between bdate and edate.

Usage

```
aqs_qa_annualperformanceeval_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.

```
aqsa_qa_annualperformanceeval_by_pqao
      aqsa_qa_annualperformanceeval_by_pqao
```

Description

[Stable] Returns quality assurance performance evaluation data - aggregated by Primary Quality Assurance Organization (PQAO) for a parameter code aggregated by matching input parameter and pqao_code for the time frame between bdate and edate.

Usage

```
aqsa_qa_annualperformanceeval_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aqsa_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the pqao_code requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_pqao functions: [aqs_qa_annualperformanceevaltransaction_by_pqao\(\)](#), [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateaudit_by_pqao\(\)](#), [aqs_qa_flowrateverification_by_pqao\(\)](#), [aqs_qa_one_point_qc_by_pqao\(\)](#), [aqs_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# Returns a tibble containing annual performance evaluation data
# for ozone where the PQAO is the Alabama Department of
# Environmental Management (pqao_code 0013).
## Not run: aqs_qa_annualperformanceeval_by_pqao(parameter = '44201',
#                                             bdate = as.Date('20170101',
#                                                         format = '%Y%m%d'),
#                                             edate = as.Date('20171231',
#                                                         format = '%Y%m%d'),
#                                             pqao_code = '0013'
#                                             )

## End(Not run)
```

aqs_qa_annualperformanceeval_by_site

aqs_qa_annualperformanceeval_by_site

Description

[Stable] Returns quality assurance performance evaluation data - aggregated by site for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame.

Usage

```
aqs_qa_annualperformanceeval_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
```

```

    countycode,
    sitenum,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_site` functions: `aqs_annualsummary_by_site()`, `aqs_dailysummary_by_site()`, `aqs_monitors_by_site()`, `aqs_qa_annualperformanceevaltransaction_by_county()`, `aqs_qa_annualperformanceevaltransaction_by_site()`, `aqs_qa_blanks_by_site()`, `aqs_qa_collocated_assessments_by_site()`, `aqs_qa_flowrateaudit_by_site()`, `aqs_qa_flowrateverification_by_site()`, `aqs_qa_one_point_qc_by_site()`, `aqs_qa_pep_audit_by_site()`, `aqs_sampledata_by_site()`, `aqs_transactionsample_by_site()`

Examples

[illegible]

bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_DataMart_APIv2` S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An `AQS_Data_Mart_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_state functions: `aqs_qa_annualperformanceevaltransaction_by_state()`, `aqs_quarterlysummary_by_box()`, `aqs_quarterlysummary_by_cbsa()`, `aqs_quarterlysummary_by_state()`, `aqs_transactionsample_by_MA()`, `aqs_transactionsample_by_state()`

Examples

[illegible]

```
aqs_qa_annualperformanceevaltransaction_by_county
      aqs_qa_annualperformanceevaltransaction_by_site
```

Description

[Stable] Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by site for a parameter code aggregated by matching input parameter, countycode and stateFIPS provided for bdate - edate time frame.

Usage

```
aqs_qa_annualperformanceevaltransaction_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data in the RD format for a single monitoring site for the countycode and stateFIPS requested for the time frame between bdate and edate in the AQS. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aqsqannualsummary_by_site\(\)](#), [aqsqdailysummary_by_site\(\)](#), [aqsqmonitors_by_site\(\)](#), [aqsqqaannualperformanceeval_by_site\(\)](#), [aqsqqaannualperformanceevaltransaction_by_site\(\)](#), [aqsqqa_blanks_by_site\(\)](#), [aqsqqa_collocated_assessments_by_site\(\)](#), [aqsqqa_flowrateaudit_by_site\(\)](#), [aqsqqa_flowrateverification_by_site\(\)](#), [aqsqqa_one_point_qc_by_site\(\)](#), [aqsqqa_pep_audit_by_site\(\)](#), [aqsqsampledata_by_site\(\)](#), [aqsqtransactionsample_by_site\(\)](#)

Examples

```
# Returns a tibble containing annual performance evaluation data
# (raw) for ozone in Baldwin County, AL for 2017 in RD format.
## Not run: aqsqaannualperformanceevaltransaction_by_county(parameter =
# 44201',
# bdate = as.Date('20170101',
# format = '%Y%m%d'),
# edate = as.Date('20171231',
# format = '%Y%m%d'),
# stateFIPS = '01',
# countycode = '003'
# )

## End(Not run)
```

```
aqsqqaannualperformanceevaltransaction_by_MA
```

```
aqsqqaannualperformanceevaltransaction_by_MA
```

Description

[Stable] Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by Monitoring agency (MA) for a parameter code aggregated by matching input parameter and MA_code provided for bdate - edate time frame.

Usage

```
aqs_qa_annualperformanceevaltransaction_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data in the AQS submissions transaction format (RD) for all sites matching the MA_code requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aqs_qa_annualperformanceeval_by_MA\(\)](#), [aqs_qa_blanks_by_MA\(\)](#), [aqs_qa_collocated_assessments_by_MA\(\)](#), [aqs_qa_flowrateaudit_by_MA\(\)](#), [aqs_qa_flowrateverification_by_MA\(\)](#)

```
aqs_qa_one_point_qc_by_MA(), aqs_qa_pep_audit_by_MA()
```

Examples

```
# Returns a tibble containing annual performance evaluation data
#   for ozone in where the MA is the Alabama Department of
#   Environmental Management (MA_code 0013) for 2017 in RD format.
## Not run: aqs_qa_annualperformanceevaltransaction_by_MA(parameter = '44201',
#                                                         bdate = as.Date('20170101',
#                                                         format = '%Y%m%d'),
#                                                         edate = as.Date('20171231',
#                                                         format = '%Y%m%d'),
#                                                         MA_code = '0013'
#                                                         )

## End(Not run)
```

```
aqs_qa_annualperformanceevaltransaction_by_pqao
      aqs_qa_annualperformanceevaltransaction_by_pqao
```

Description

[Stable] Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by Primary Quality Assurance Organization (PQAO) for a parameter code aggregated by matching input parameter and pqao_code provided for bdate - edate time frame.

Usage

```
aqs_qa_annualperformanceevaltransaction_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.

pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aqs_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_pqao functions: [aqs_qa_annualperformanceeval_by_pqao\(\)](#), [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateaudit_by_pqao\(\)](#), [aqs_qa_flowrateverification_by_pqao\(\)](#), [aqs_qa_one_point_qc_by_pqao\(\)](#), [aqs_qa_pep_audit_by_pqao\(\)](#)

Examples

```
#Returns a tibble containing annual performance evaluation data for
# ozone in where the PQA0 is the Alabama Department of
# Environmental Management (pqao_code 0013) for 2017 in RD format.
## Not run: aqs_qa_annualperformanceevaltransaction_by_pqao(parameter =
# 44201,
# bdate = as.Date('20170101',
#   format = '%Y%m%d'),
# edate = as.Date('20171231',
#   format = '%Y%m%d'),
# pqao_code = '0013'
# )

## End(Not run)
```

aqsqqaannualperformanceevaltransaction_by_site

aqsqqaannualperformanceevaltransaction_by_site

Description

[Stable] Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by site for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame.

Usage

```
aqsqqaannualperformanceevaltransaction_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsqstates() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqsqcounties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqsqsites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance annual performance evaluation data in the RD format for a single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate in the AQS. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aqsqannualsummary_by_site\(\)](#), [aqsqdailysummary_by_site\(\)](#), [aqsqmonitors_by_site\(\)](#), [aqsqqaannualperformanceeval_by_site\(\)](#), [aqsqqaannualperformanceevaltransaction_by_site\(\)](#), [aqsqqa_blanks_by_site\(\)](#), [aqsqqa_collocated_assessments_by_site\(\)](#), [aqsqqa_flowrateaudit_by_site\(\)](#), [aqsqqa_flowrateverification_by_site\(\)](#), [aqsqqa_one_point_qc_by_site\(\)](#), [aqsqqa_pep_audit_by_site\(\)](#), [aqsqsampledata_by_site\(\)](#), [aqsqtransactionsample_by_site\(\)](#)

Examples

```
#Returns a tibble containing annual performance evaluation data
# (raw) for ozone at the Fairhope site in Baldwin County, AL for
# 2017 in RD format.
## Not run: aqsqqaannualperformanceevaltransaction_by_site(parameter = '44201',
#                                     bdate = as.Date('20170101',
#                                     format = '%Y%m%d'),
#                                     edate = as.Date('20171231',
#                                     format = '%Y%m%d'),
#                                     stateFIPS = '01',
#                                     countycode = '003',
#                                     sitenum = '0010'
#                                     )

## End(Not run)
```

aqsqqaannualperformanceevaltransaction_by_state

aqsqqaannualperformanceevaltransaction_by_state

Description

[Stable] Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by state for a parameter code aggregated by matching input parameter and stateFIPS provided for bdate - edate time frame.

Usage

```
aqsqqa_annualperformanceevaltransaction_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsqstates() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5

second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_state` functions: [aq_s_qa_annualperformanceeval_by_state\(\)](#), [aq_s_quarterlysummary_by_box\(\)](#), [aq_s_quarterlysummary_by_cbsa\(\)](#), [aq_s_quarterlysummary_by_state\(\)](#), [aq_s_transactionsample_by_MA\(\)](#), [aq_s_transactionsample_by_state\(\)](#)

Examples

```
# Returns a tibble containing annual performance evaluation data
# for ozone in Alabmba for 2017 in RD format.
## Not run:
aqs_qa_annualperformanceevaltransaction_by_state(parameter = '44201',
                                                  bdate = as.Date('20170101',
                                                                format = '%Y%m%d'),
                                                  edate = as.Date('20171231',
                                                                format = '%Y%m%d'),
                                                  stateFIPS = '01'
                                                  )

## End(Not run)
```

aq_s_qa_blanks_by_county

aq_s_qa_blanks_by_county

Description

[Stable] Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the county level.

Usage

```
aqs_qa_blanks_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsqstates() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqsqcounties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input stateFIPS and countycode. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqsqannualsummary_by_county\(\)](#), [aqsqdailysummary_by_county\(\)](#), [aqsqmonitors_by_county\(\)](#), [aqsqqa_annualperformanceeval_by_county\(\)](#), [aqsqqa_collocated_assessments_by_county\(\)](#), [aqsqqa_flowrateaudit_by_county\(\)](#), [aqsqqa_flowrateverification_by_county\(\)](#), [aqsqqa_one_point_qc_by_county\(\)](#), [aqsqqa_pep_audit_by_county\(\)](#), [aqsqquarterlysummary_by_county\(\)](#), [aqsqquarterlysummary_by_site\(\)](#), [aqsqsampledata_by_county\(\)](#), [aqsqtransactionsample_by_county\(\)](#)

Examples

```
# returns a tibble with PM2.5 blank data for
#   Colbert County, AL for January 2018
## Not run: aqsqqa_blanks_by_county(parameter = '88101',
```

```

                                bdate = as.Date('20170101',
                                                format='%Y%m%d'),
                                edate = as.Date('20190131',
                                                format='%Y%m%d'),
                                stateFIPS = '01',
                                countycode = '033'
                                )

## End(Not run)
```

aqs_qa_blanks_by_MA	<i>aqs_qa_blanks_by_MA</i>
---------------------	----------------------------

Description

[Stable] Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated by monitoring agency code (MA_code).

Usage

```
aqs_qa_blanks_by_MA(parameter, bdate, edate, MA_code, return_header = FALSE)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input MA_code. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_MA functions: [aqs_qa_annualperformanceeval_by_MA\(\)](#), [aqs_qa_annualperformanceevaltrans_by_MA\(\)](#), [aqs_qa_collocated_assessments_by_MA\(\)](#), [aqs_qa_flowrateaudit_by_MA\(\)](#), [aqs_qa_flowrateverification_by_MA\(\)](#), [aqs_qa_one_point_qc_by_MA\(\)](#), [aqs_qa_pep_audit_by_MA\(\)](#)

Examples

```
# Returns a tibble containing PM2.5 blank data in
# January 2018 where the Monitoring Agency is the Alabama
# Department of Environmental Management (agency 0013)
## Not run: aqs_qa_blanks_by_MA(parameter = '88101',
                                bdate = as.Date('20170101',
                                                  format = '%Y%m%d'),
                                edate = as.Date('20190131',
                                                  format = '%Y%m%d'),
                                MA_code = '0013'
                                )

## End(Not run)
```

aqs_qa_blanks_by_pqao *aqs_qa_blanks_by_pqao*

Description

[Stable] Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated by Primary Quality Assurance Organization (PQAO).

Usage

```
aqs_qa_blanks_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```



```
                                format = '%Y%m%d'),
                                pqao_code = '0013'
                                )

## End(Not run)
```

```
aqs_qa_blanks_by_site  aqs_qa_blanks_by_site
```

Description

[Stable] Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the site level.

Usage

```
aqs_qa_blanks_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_annualperformanceeval_by_site\(\)](#), [aq_s_qa_annualperformanceevaltransaction_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```
#Returns a tibble of PM2.5 blank
# data for the Muscle Shoals site (#0014) in Colbert County, AL
# for January 2018
## Not run:
aqs_qa_blanks_by_site(parameter = '88101',
                      bdate = as.Date('20170101',
                                       format='%Y%m%d'),
                      edate = as.Date('20190131',
                                       format='%Y%m%d'),
                      stateFIPS = '01',
                      countycode = '033',
                      sitenum = '1002'
                      )

## End(Not run)
```

aq_s_qa_blanks_by_state

aq_s_qa_blanks_by_state

Description

[Stable] Returns a table of blank quality assurance data . Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the state level.

Usage

```
aq_s_qa_blanks_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aq_s_states() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input stateFIPS. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqs_annualsummary_by_state\(\)](#), [aqs_dailysummary_by_state\(\)](#), [aqs_monitors_by_state\(\)](#), [aqs_qa_collocated_assessments_by_state\(\)](#), [aqs_qa_flowrateaudit_by_state\(\)](#), [aqs_qa_flowrateverification_by_state\(\)](#), [aqs_qa_one_point_qc_by_state\(\)](#), [aqs_qa_pep_audit_by_state\(\)](#), [aqs_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble which contains PM2.5 blank data
# for Alabama for January 2018
## Not run: aqs_qa_blanks_by_state(parameter = '88101',
                                bdate = as.Date('20180101',
                                                format = '%Y%m%d'
                                                ),
                                edate = as.Date('20180131',
                                                format = '%Y%m%d'),
                                stateFIPS = '01'
                                )

## End(Not run)
```

```
aqs_qa_collocated_assessments_by_county
```

```
aqs_qa_collocated_assessments_by_county
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS and county_code provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.


```

),
stateFIPS = '01',
countycode = '089'
)

## End(Not run)

```

aqs_qa_collocated_assessments_by_MA

aqs_qa_collocated_assessments_by_MA

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

Usage

```

aqs_qa_collocated_assessments_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a monitoring agency. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_MA functions: [aqsqaqannualperformanceevalbyMA\(\)](#), [aqsqaqannualperformanceevaltransbyMA\(\)](#), [aqsqaqblanksbyma\(\)](#), [aqsqaqflowrateauditbyMA\(\)](#), [aqsqaqflowrateverificationbyMA\(\)](#), [aqsqaqonepointqcbyMA\(\)](#), [aqsqaqpepauditbyMA\(\)](#)

Examples

```
# Returns a tibble containing collocated assessment
#   data for FRM PM2.5 January 2013 where the Monitoring Agency is
#   the Alabama Department of Environmental Management
# (agency 0013)
## Not run: aqsqaqacollocatedassessmentsbyMA(parameter='88101',
#                                             bdate = as.Date('20130101',
#                                                         format = '%Y%m%d'),
#                                             edate = as.Date('20150131',
#                                                         format = '%Y%m%d'),
#                                             MA_code = '0013'
#                                             )

## End(Not run)
```

aqsqaqacollocatedassessmentsbypqao

aqsqaqacollocatedassessmentsbypqao

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, and Primary Quality Assurance Organisation (PQAO) code provided for bdate - edate time frame.

Usage

```
aqsqaqacollocatedassessmentsbypqao(
  parameter,
  bdate,
  edate,
  pqao_code,
```

```

    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aq_s_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a pqao. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aq_s_qa_annualperformanceeval_by_pqao\(\)](#), [aq_s_qa_annualperformanceevaltr_by_pqao\(\)](#), [aq_s_qa_blanks_by_pqao\(\)](#), [aq_s_qa_flowrateaudit_by_pqao\(\)](#), [aq_s_qa_flowrateverification_by_pqao\(\)](#), [aq_s_qa_one_point_qc_by_pqao\(\)](#), [aq_s_qa_pep_audit_by_pqao\(\)](#)

Examples

```

# Returns a tibble of collocated assessment
# data for FRM PM2.5 in January 2013 where the PQA0 is the Alabama
# Department of Environmental Management (agency 0013)
## Not run: aqs_qa_collocated_assessments_by_pqao(parameter = '88101',

```

```

        bdate = as.Date('20130101',
                        format = '%Y%m%d'),
        edate = as.Date('20150131',
                        format = '%Y%m%d'),
        pqao_code = '0013'
    )

## End(Not run)

```

```

aqs_qa_collocated_assessments_by_site
      aqs_qa_collocated_assessments_by_site

```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame.

Usage

```

aqs_qa_collocated_assessments_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.

Value

Note

See Also

Examples

[illegible]

```
aqs_qa_collocated_assessments_by_state
      aqs_qa_collocated_assessments_by_state
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter and stateFIPS provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a state. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqs_annualsummary_by_state\(\)](#), [aqs_dailysummary_by_state\(\)](#), [aqs_monitors_by_state\(\)](#), [aqs_qa_blanks_by_state\(\)](#), [aqs_qa_flowrateaudit_by_state\(\)](#), [aqs_qa_flowrateverification_by_state\(\)](#), [aqs_qa_one_point_qc_by_state\(\)](#), [aqs_qa_pep_audit_by_state\(\)](#), [aqs_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of collocated
# assessment data for FRM2.5 for January 2013
## Not run: aqs_qa_collocated_assessments_by_state(parameter='88101',
                                                    bdate = as.Date('20130101',
                                                    format = '%Y%m%d'
                                                    ),
                                                    edate = as.Date('20150131',
                                                    format = '%Y%m%d'
                                                    ),
                                                    stateFIPS = '01'
                                                    )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_county
      aqs_qa_flowrateaudit_by_county
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS and countycode for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_county(
  parameter,
  bdate,
  edate,
```

```

    stateFIPS,
    countycode,
    return_header
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing flow rate audit data for the requested countycode and stateFIPS. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqs_annualsummary_by_county\(\)](#), [aqs_dailysummary_by_county\(\)](#), [aqs_monitors_by_county\(\)](#), [aqs_qa_annualperformanceeval_by_county\(\)](#), [aqs_qa_blanks_by_county\(\)](#), [aqs_qa_collocated_assessments_by_county\(\)](#), [aqs_qa_flowrateverification_by_county\(\)](#), [aqs_qa_one_point_qc_by_county\(\)](#), [aqs_qa_pep_audit_by_county\(\)](#), [aqs_quarterlysummary_by_county\(\)](#), [aqs_quarterlysummary_by_site\(\)](#), [aqs_sampledata_by_county\(\)](#), [aqs_transactionsample_by_county\(\)](#)

Examples

```
#Returns a tibble of flow rate audit data for
# Jefferson County, AL for January 2018
## Not run: aqs_qa_flowrateaudit_by_county(parameter = '88101',
                                           bdate = as.Date('20170101',
                                                           format='%Y%m%d'),
                                           edate = as.Date('20190131',
                                                           format = '%Y%m%d'),
                                           tateFIPS = '01',
                                           countycode = '073'
                                           )

## End(Not run)
```

aq _s _qa_flowrateaudit_by_MA
<i>aq_s_qa_flowrateaudit_by_MA</i>

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and monitoring agency code (*_by_MA*) for *bdate* - *edate* time frame.

Usage

```
aqs_qa_flowrateaudit_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

Arguments

<i>parameter</i>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<i>bdate</i>	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
<i>edate</i>	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
<i>MA_code</i>	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aq_s_mas() for a list of all Monitoring Agency (MA) codes and names available,
<i>return_header</i>	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing flow rate audit data for the requested MA_code. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aqsq_annualperformanceeval_by_MA\(\)](#), [aqsq_annualperformanceevaltrans_by_MA\(\)](#), [aqsq_blanks_by_MA\(\)](#), [aqsq_collocated_assessments_by_MA\(\)](#), [aqsq_flowrateverification_by_MA\(\)](#), [aqsq_one_point_qc_by_MA\(\)](#), [aqsq_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble of flow rate audit data
#   for FRM PM2.5 January 2016 - Januray 2018 where the Monitoring Agency is
#   the Jefferson County, AL Department of Health (agency 0550)
## Not run: aqsqa_flowrateaudit_by_MA(parameter = '88101',
                                     bdate = as.Date('20160101',
                                     format = '%Y%m%d'),
                                     edate = as.Date('20180131',
                                     format = '%Y%m%d'),
                                     MA_code = '0550'
                                     )

## End(Not run)
```

aqsq_flowrateaudit_by_pqao

aqsq_flowrateaudit_by_pqao

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and Primary Quality Assurance Organization (PQAO) code for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aqs_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing flow rate audit data for the requested pqao_code. An AQS_DataMart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aqs_qa_annualperformanceeval_by_pqao\(\)](#), [aqs_qa_annualperformanceevaltr_by_pqao\(\)](#), [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateverification_by_pqao\(\)](#), [aqs_qa_one_point_qc_by_pqao\(\)](#), [aqs_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# Returns a tibble of flow rate audit data for January
# 2018 where the PQA0 is the Jefferson County, AL Department of
# Health (agency 0550).
## Not run: aqs_qa_flowrateaudit_by_pqao(parameter = '88101',
                                         bdate = as.Date('20170101',
                                                         format = '%Y%m%d'),
                                         edate = as.Date('20180131',
                                                         format = '%Y%m%d'),
                                         pqao_code = '0550'
                                         )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_site
      aqs_qa_flowrate audit_by_site
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS, countycode and site number for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.


```

    )

## End(Not run)

```

```

aqsq_flowrateaudit_by_state
  aqsq_flowrateaudit_by_state

```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and stateFIPS for bdate - edate time frame.

Usage

```

aqsq_flowrateaudit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsq_states() for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing flow rate audit data for the requested stateFIPS. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqs_annualsummary_by_state\(\)](#), [aqs_dailysummary_by_state\(\)](#), [aqs_monitors_by_state\(\)](#), [aqs_qa_blanks_by_state\(\)](#), [aqs_qa_collocated_assessments_by_state\(\)](#), [aqs_qa_flowrateverification_by_state\(\)](#), [aqs_qa_one_point_qc_by_state\(\)](#), [aqs_qa_pep_audit_by_state\(\)](#), [aqs_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of flow rate audit
# data for Alabama in January 2018
## Not run: aqs_qa_flowrateaudit_by_state(parameter = '88101',
                                         bdate = as.Date('20170101',
                                                         format = '%Y%m%d'),
                                         edate = as.Date('20180131',
                                                         format = '%Y%m%d'),
                                         stateFIPS = '01'
                                         )

## End(Not run)
```

aqs_qa_flowrateverification_by_county

aqs_qa_flowrateverification_by_county

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, stateFIPS, and county_code, provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
```

```
    return_header = FALSE
  )
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a county. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqs_annualsummary_by_county\(\)](#), [aqs_dailysummary_by_county\(\)](#), [aqs_monitors_by_county\(\)](#), [aqs_qa_annualperformanceeval_by_county\(\)](#), [aqs_qa_blanks_by_county\(\)](#), [aqs_qa_collocated_assessments_by_county\(\)](#), [aqs_qa_flowrateaudit_by_county\(\)](#), [aqs_qa_one_point_qc_by_county\(\)](#), [aqs_qa_pep_audit_by_county\(\)](#), [aqs_quarterlysummary_by_county\(\)](#), [aqs_quarterlysummary_by_site\(\)](#), [aqs_sampledata_by_county\(\)](#), [aqs_transactionsample_by_county\(\)](#)

Examples

```
# returns a tibble of flow rate verification data for
#   Colbert County, AL for January 2018
## Not run: aqs_qa_flowrateverification_by_county(parameter = '88101',
                                                    bdate = as.Date('20180101',
                                                                    format = '%Y%m%d'
                                                                    ),
                                                    edate = as.Date('20190131',
                                                                    format = '%Y%m%d'
                                                                    ),
                                                    stateFIPS = '01',
                                                    countycode = '033'
                                                    )

## End(Not run)
```

```
aqs_qa_flowrateverification_by_MA
      aqs_qa_flowrateverification_by_MA
```

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,

<code>return_header</code>	If FALSE (default) only returns data requested. If TRUE returns a <code>AQSAPI_v2</code> object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.
----------------------------	---

Value

a tibble or an `AQS_DataMart_APIv2` S3 object containing quality assurance flow rate verification data for monitors within a Monitoring agency. An `AQS_DataMart_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_MA` functions: `aqs_qa_annualperformanceeval_by_MA()`, `aqs_qa_annualperformanceevaltrans`, `aqs_qa_blanks_by_MA()`, `aqs_qa_collocated_assessments_by_MA()`, `aqs_qa_flowrateaudit_by_MA()`, `aqs_qa_one_point_gc_by_MA()`, `aqs_qa_pep_audit_by_MA()`

Examples

[illegible]

```
aqs_qa_flowrateverification_by_pqao
      aqs_qa_flowrateverification_by_pqao
```

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and Primary Quality Assurance Organization (PQAO) code provided for bdate - edate time.

Usage

```
aqs_qa_flowrateverification_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aqs_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a pqao. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.


```

    edate,
    stateFIPS,
    countycode,
    sitenum,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance flow rate verification data for monitors at a site. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aqs_annualsummary_by_site\(\)](#), [aqs_dailysummary_by_site\(\)](#), [aqs_monitors_by_site\(\)](#), [aqs_qa_annualperformanceeval_by_site\(\)](#), [aqs_qa_annualperformanceevaltransaction_by_site\(\)](#), [aqs_qa_blanks_by_site\(\)](#), [aqs_qa_collocated_assessment_by_site\(\)](#), [aqs_qa_flowrateaudit_by_site\(\)](#), [aqs_qa_one_point_qc_by_site\(\)](#), [aqs_qa_pep_audit_by_site\(\)](#), [aqs_sampledata_by_site\(\)](#), [aqs_transactionsample_by_site\(\)](#)

Examples

```
# returns a tibble of flow rate verification
#   data for the Muscle Shoals site (#1002) in Colbert County, AL
#   for January 2018:
## Not run: aqs_qa_flowrateverification_by_site(parameter = '88101',
#                                               bdate = as.Date('20170101',
#                                                             format = '%Y%m%d'),
#                                               edate = as.Date('20180131',
#                                                             format = '%Y%m%d'),
#                                               stateFIPS = '01',
#                                               countycode = '033',
#                                               sitenum = '1002'
#                                               )

## End(Not run)
```

aqs_qa_flowrateverification_by_state

aqs_qa_flowrateverification_by_state

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, and stateFIPS, provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
-----------	---


```

)

## End(Not run)

```

```

aqs_qa_one_point_qc_by_county
  aqs_qa_one_point_qc_by_county_

```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object containing one point QC check data aggregated by county_code.

Usage

```

aqs_qa_one_point_qc_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing one point qc data within a county. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_county` functions: `aqs_annualsummary_by_county()`, `aqs_dailysummary_by_county()`, `aqs_monitors_by_county()`, `aqs_qa_annualperformanceeval_by_county()`, `aqs_qa_blanks_by_county()`, `aqs_qa_collocated_assessments_by_county()`, `aqs_qa_flowrateaudit_by_county()`, `aqs_qa_flowrateverification_by_county()`, `aqs_qa_pep_audit_by_county()`, `aqs_quarterlysummary_by_county()`, `aqs_quarterlysummary_by_site()`, `aqs_sampledata_by_county()`, `aqs_transactionsample_by_county()`

Examples

```
#returns a tibble of One Point QC data for ozone
# in Barnstable County, MA for January 2018
## Not run: aqs_qa_one_point_qc_by_county(parameter= '44201',
                                           bdate = as.Date('20170101',
                                                             format = '%Y%m%d'),
                                           edate = as.Date('20180131',
                                                             format = '%Y%m%d'),
                                           stateFIPS = '25',
                                           countycode = '001'
                                           )

## End(Not run)
```

aqs_qa_one_point_qc_by_MA

aqs_qa_one_point_qc_by_MA

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object containing one point QC check data aggregated by monitoring agency code (`_by_MA`).

Usage

```
aqs_qa_one_point_qc_by_MA(
  parameter,
  bdate,
  edate,
```

```

    MA_code,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqsmas() for a list of all Monitoring Agency (MA) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing one point qc data for a single monitoring agency. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aqsq_a_annualperformanceeval_by_MA\(\)](#), [aqsq_a_annualperformanceevaltrans_by_MA\(\)](#), [aqsq_a_blanks_by_MA\(\)](#), [aqsq_a_collocated_assessments_by_MA\(\)](#), [aqsq_a_flowrateaudit_by_MA\(\)](#), [aqsq_a_flowrateverification_by_MA\(\)](#), [aqsq_a_pep_audit_by_MA\(\)](#)

Examples

```

# returns a tibble of ozone One Point QC data
# in January 2018 where the Monitoring Agency is the
# Massachusetts Department of Environmental Protection

```

```

# (agency 0660)
## Not run: aqs_qa_one_point_qc_by_MA(parameter = '44201',
                                     bdate = as.Date('20170101',
                                                       format = '%Y%m%d'),
                                     edate = as.Date('20180131',
                                                       format = '%Y%m%d'),
                                     MA_code = '0660'
                                     )

## End(Not run)

```

```
aqs_qa_one_point_qc_by_pqao
```

```
aqs_qa_one_point_qc_by_pqao
```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object containing Quality assurance data - collocated assessment raw data aggregated by Primary Quality Assurance Organization (PQAO) code.

Usage

```

aqs_qa_one_point_qc_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aq_s_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing one point qc data within a pqao. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aqs_qa_annualperformanceeval_by_pqao\(\)](#), [aqs_qa_annualperformanceevaltr](#), [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateaudit_by_pqao\(\)](#), [aqs_qa_flowrateverification_by_pqao\(\)](#), [aqs_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# returns a tibble of ozone One Point QC
# data for Jan 2017 - January 2018 where the PQAO is the Massachusetts
# Department of Environmental Protection (agency 0660)
## Not run: aqs_qa_one_point_qc_by_pqao(parameter = '88101',
                                     bdate = as.Date('20170101',
                                     format = '%Y%m%d'),
                                     edate = as.Date('20180131',
                                     format = '%Y%m%d'),
                                     pqao_code = '0660'
                                     )

## End(Not run)
```

```
aqs_qa_one_point_qc_by_site
      aqs_qa_one_point_qc_by_site
```

Description

[Stable] Returns a table of one point QC raw data aggregated by parameter code, stateFIPS, countycode and site number.

Usage

```
aqs_qa_one_point_qc_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing one point qc data for the requested site. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API

calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_site` functions: `aqsaannualsummary_by_site()`, `aqsdailysummary_by_site()`, `aqsmonitors_by_site()`, `aqsaqaannualperformanceeval_by_site()`, `aqsaqaannualperformanceevaltransaction_by_site()`, `aqsaqaannualperformanceevaltransaction_by_site()`, `aqsaqa_blanks_by_site()`, `aqsaqa_collocated_assessment_by_site()`, `aqsaqa_flowrateaudit_by_site()`, `aqsaqa_flowrateverification_by_site()`, `aqsaqa_pep_audit_by_site()`, `aqsa_sampladata_by_site()`, `aqsa_transactionsample_by_site()`

Examples

```
# returns a tibble of One Point QC data for
#   ozone at the Truro National Seashore site (\#0002) in
#   Barnstable County, MA for January 2018:
## Not run: aqsaqa_one_point_qc_by_site(parameter = '44201',
#                                       bdate = as.Date('20180101',
#                                                         format = '%Y%m%d'),
#                                       edate = as.Date('20180131',
#                                                         format = '%Y%m%d'),
#                                       stateFIPS = '25',
#                                       countycode = '001',
#                                       sitenum = '0002'
#                                       )

## End(Not run)
```

```
aqsaqa_one_point_qc_by_state
      aqsaqa_one_point_qc_by_state
```

Description

[Stable] Returns a tibble or an `AQS_DataMart_APIv2` S3 object containing Quality assurance data - flow rate audit raw data aggregated by state FIPS.

Usage

```
aqsaqa_one_point_qc_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```



```

                                format = '%Y%m%d'
                                ),
                                stateFIPS = '25'
                                )

## End(Not run)

```

```

aqs_qa_pep_audit_by_county
    aqs_qa_pep_audit_by_county

```

Description

[**Stable**] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS and countycode for the time frame between bdate and edate.

Usage

```

aqs_qa_pep_audit_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance PEP audit data within a county. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_annualperformanceeval_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_quarterlysummary_by_county\(\)](#), [aq_s_quarterlysummary_by_site\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns a tibble with PEP Audit data for FRM
# PM2.5 in Madison County, AL for 2017
## Not run: aqs_qa_pep_audit_by_county_multiyear(parameter = '88101',
                                                bdate = as.Date('20150101',
                                                                format = '%Y%m%d'
                                                                ),
                                                edate = as.Date('20171231',
                                                                format = '%Y%m%d'
                                                                ),
                                                stateFIPS = '01',
                                                countycode = '089'
                                                )

## End(Not run)
```

aq_s_qa_pep_audit_by_MA

aq_s_qa_pep_audit_by_MA

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by monitoring agency code (_by_MA) for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_MA(parameter, bdate, edate, MA_code, return_header = FALSE)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance PEP audit data for a monitoring agency. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aqs_qa_annualperformanceeval_by_MA\(\)](#), [aqs_qa_annualperformanceevaltrans](#), [aqs_qa_blanks_by_MA\(\)](#), [aqs_qa_collocated_assessments_by_MA\(\)](#), [aqs_qa_flowrateaudit_by_MA\(\)](#), [aqs_qa_flowrateverification_by_MA\(\)](#), [aqs_qa_one_point_qc_by_MA\(\)](#)

Examples

```
# Returns a tibble of PEP audit data for
#   June 2017 where the Monitoring Agency is the Alabama Department
#   of Environmental Management (agency 0013)
```

```

## Not run: aqs_qa_pep_audit_by_MA(parameter = '88101',
                                bdate = as.Date('20170601',
                                                format = '%Y%m%d'),
                                edate = as.Date('20170630',
                                                format = '%Y%m%d'),
                                MA_code = '0013'
                                )

## End(Not run)

```

```

aqs_qa_pep_audit_by_pqao
      aqs_qa_pep_audit_by_pqao

```

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by Primary Quality Assurance Organization (PQAO) code for the time frame between bdate and edate.

Usage

```

aqs_qa_pep_audit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes). Use aqs_pqaos() for a list of all Primary Quality Assurance Organization (pqao) codes and names available,
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance PEP audit data for a Primary Quality Assurance Organization. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_pqao functions: [aqs_qa_annualperformanceeval_by_pqao\(\)](#), [aqs_qa_annualperformanceevaltr_by_pqao\(\)](#), [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateaudit_by_pqao\(\)](#), [aqs_qa_flowrateverification_by_pqao\(\)](#), [aqs_qa_one_point_qc_by_pqao\(\)](#)

Examples

```
# returns a tibble of PEP audit data for
#   June 2017 where the pqao is the Alabama Department of
#   Environmental Management (agency 0013)
## Not run: aqs_qa_pep_audit_by_pqao(parameter = '88101',
                                   bdate = as.Date('20170601',
                                                    format = '%Y%m%d'
                                                    ),
                                   edate = as.Date('20190630',
                                                    format = '%Y%m%d'),
                                   pqao_code = '0013'
                                   )

## End(Not run)
```

aqs_qa_pep_audit_by_site

aqs_qa_pep_audit_by_site

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS, countycode and site number for the time frame between bdate and edate.

Usage

```
aqsa_qa_pep_audit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqsa_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqsa_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqsa_sites_by_county() for the list of available site numbers in given county and state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object containing quality assurance PEP audit data within a site. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to

retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_site` functions: `aqs_annualsummary_by_site()`, `aqs_dailysummary_by_site()`, `aqs_monitors_by_site()`, `aqs_qa_annualperformanceeval_by_site()`, `aqs_qa_annualperformanceevaltransaction_by_site()`, `aqs_qa_blanks_by_site()`, `aqs_qa_collocated_assessment_by_site()`, `aqs_qa_flowrateaudit_by_site()`, `aqs_qa_flowrateverification_by_site()`, `aqs_qa_one_point_qc_by_site()`, `aqs_sampledata_by_site()`, `aqs_transactionsample_by_site()`

Examples

```
# returns a tibble of pep Audit data for FRM PM2.5
#   at the Huntsville Old Airport site (\#0014) in Madison County,
#   AL for 2017 - 2019.
## Not run: aqs_qa_pep_audit_by_site(parameter = '88101',
#                                     bdate = as.Date('20170101',
#                                                       format = '%Y%m%d'),
#                                     edate = as.Date('20191231',
#                                                       format = '%Y%m%d'),
#                                     stateFIPS = '01',
#                                     countycode = '089',
#                                     sitenum = '0014'
#                                     )

## End(Not run)
```

aqs_qa_pep_audit_by_state	
	<i>aqs_qa_pep_audit_by_state</i>

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, and stateFIPS for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```



```

stateFIPS='01'
)

## End(Not run)

```

```

aqs_quarterlysummary_by_box
aqs_quarterlysummary_by_box

```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object of quarterly summary data aggregated by and area within a latitude/longitude bounding box.

Usage

```

aqs_quarterlysummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object that represents the minimum latitude of a geographic box. Decimal latitude with north being positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north being positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.

maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that contains quarterly summary statistics for an area within a latitude/longitude bounding box. An AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of quarterly summary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $n + 5$ seconds).

Also note that for quarterly data, only the year portion of the bdate and edate are used and all 4 quarters in the year are returned.

See Also

Other Aggregate _by_state functions: [aq_s_qa_annualperformanceeval_by_state\(\)](#), [aq_s_qa_annualperformanceeval_by_state\(\)](#), [aq_s_quarterlysummary_by_cbsa\(\)](#), [aq_s_quarterlysummary_by_state\(\)](#), [aq_s_transactionsample_by_MA\(\)](#), [aq_s_transactionsample_by_state\(\)](#)

Examples

```
# Returns a tibble containing ozone quarterly summaries
#   in the vicinity of central Alabama for each quarter in
#   between 2015 - 2017
## Not run: aqs_quarterlysummary_by_box(parameter = '44201',
```

```

        bdate = as.Date('20150101',
                        format = '%Y%m%d'),
        edate = as.Date('20171231',
                        format = '%Y%m%d'),
        minlat = '33.3',
        maxlat = '33.6',
        minlon = '-87.0',
        maxlon = '-86.7'
    )

## End(Not run)

```

```

aqs_quarterlysummary_by_cbsa
      aqs_quarterlysummary_by_cbsa

```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object of quarterly summary data aggregated by stateFIPS.

Usage

```

aqs_quarterlysummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros). Use aqs_cbsas() for a list of all CBSA codes and names available,
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

```
aqs_quarterlysummary_by_county
      aqs_quarterlysummary_by_county
```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object of quarterly summary data aggregated by cbsa (Core Based Statistical Area) code.

Usage

```
aqs_quarterlysummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

```
aqs_quarterlysummary_by_site
      aqs_quarterlysummary_by_site
```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object of quarterly summary data aggregated by site with the provided parameternum, stateFIPS, county_code, and sitenum for bdate - edate time frame.

Usage

```
aqs_quarterlysummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.


```

                                sitenum = '0014'
                                )

## End(Not run)

```

```

aqs_quarterlysummary_by_state
      aqs_quarterlysummary_by_state

```

Description

[Stable] Returns a tibble or an AQS_DataMart_APIv2 S3 object of quarterly summary data aggregated by stateFIPS.

Usage

```

aqs_quarterlysummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

aq_removeheader	<i>aq_removeheader</i>
-----------------	------------------------

Description

[Stable] Coerces a single AQS_Data_Mart_APIv2 S3 object or a list of AQS_Data_Mart_APIv2 S3 objects into a single tibble object. This function decouples the \$Data from the AQSAPI_v2 object and returns only the \$Data portion as a tibble. If the input is a list of AQSAPI_v2 objects combines the \$Data portion of each AQS_Data_Mart_APIv2 S3 object into a single tibble with \$Header information discarded. Else returns the input with no changes.

Usage

```
aq_removeheader(.AQSubject)
```

Arguments

.AQSubject	A 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.
------------	--

Value

a tibble of the combined \$data portions of the input AQS_Data_Mart_APIv2 S3 object with the \$Header portion discarded.

Note

Since this function returns only the \$Data portion of RAQSAPI_v2 objects this means that the \$Header information will not be present in the object being returned.

Examples

```
#coerce a AQS_Data_MART_APIv2 object to a single tibble.
## Not run: aq_removeheader(AQSubject)
```

aq_revisionhistory	<i>aq_revisionhistory</i>
--------------------	---------------------------

Description

[Stable] Returns the change history to the AQS Data Mart API.

Usage

```
aq_revisionhistory(return_header = FALSE)
```

Arguments

`return_header` If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object that is the return value from the AQS API. A AQS_DataMart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Examples

```
# Returns a DataFrame of the EPA AQS Data Mart API revision history
# \dontrun{ aqs_revisionHistory() }
```

```
aqs_sampladata_by_box  aq_sampladata_by_box
```

Description

[Stable] Returns sample data where the data is aggregated by latitude/longitude bounding box (`_by_box`). If `return_header` is FALSE (default) this function returns a single dataframe with the requested data. If `return_header` is TRUE returns a list of AQSAPI_v2 objects where each index of the list is an individual RAQSAPI_v2 object returned from each successive call to the AQS API. RAQSAPI_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter and cbsa_code provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call /(useful for debugging/). This function returns NULL is bdate > edate.

Usage

```
aqs_sampladata_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  duration = NA_character_,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object that represents the minimum latitude of a geographic box. Decimal latitude with north being positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north being positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. Use aq_sampl durations() for a list of all available duration codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors within the input latitude/longitude bounding box for a single parameter. An AQS_DataMart_APIv2 is a 2 item named list in which the first item */(\$Header/)* is a tibble of header information from the AQS API and the second item */(\$Data/)* is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_box functions: [aq_annualsummary_by_box\(\)](#), [aq_monitors_by_box\(\)](#)

Examples

```
# Returns a tibble containing all ozone samples
# in the vicinity of central Alabama between
# May 1, 2015 - May 2, 2017
## Not run: aq_sampladata_by_box(parameter = '44201',
                                bdate = as.Date('20150501',
                                                  format = '%Y%m%d'),
                                edate = as.Date('20170502',
                                                  format = '%Y%m%d'),
                                minlat = '33.3',
                                maxlat = '33.6',
                                minlon = '-87.0',
                                maxlon = '-86.7'
                                )

## End(Not run)
```

aq_sampladata_by_cbsa

aq_sampladata_by_cbsa

Description

[Stable] Returns sample data where the data is aggregated at the Core Based Statistical Area (cbsa) level. If return_header is FALSE (default) this function returns a single dataframe with the requested data. If return_header is TRUE returns a list of AQSAPI_v2 objects where each index of the list is an individual RAQSAPI_v2 object returned from each successive call to the AQS API. RAQSAPI_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter and cbsa_code provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call (useful for debugging/). This function returns NULL is bdate > edate.

Usage

```
aq_sampladata_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  duration = NA_character_,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros). Use aq_sbsas() for a list of all CBSA codes and names available,
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. Use aq_sampl durations() for a list of all available duration codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors matching cbsa_code for the given parameter. An AQS_DataMart_APIv2 is a 2 item named list in which the

first item `/(($Header/)` is a tibble of header information from the AQS API and the second item `/(($Data/)` is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampled data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQS API retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time `/(Big O notation:  $O(n + 5 \text{ seconds})$ /)`

See Also

Other Aggregate `_by_cbsa` functions: [aq_sampladata_by_cbsa\(\)](#), [aq_sampladata_by_cbsa\(\)](#), [aq_sampladata_by_cbsa\(\)](#)

Examples

```
# returns tibble which contains $NO_{2}$ data
# for Charlotte-Concord-Gastonia, NC cbsa for
# January 1, 2015 - January 01, 2017
## Not run: aq_sampladata_by_cbsa(parameter = '42602',
                                bdate = as.Date('20150101',
                                                format = '%Y%m%d'),
                                edate = as.Date('20170101',
                                                format = '%Y%m%d'),
                                cbsa_code = '16740'
                                )

## End(Not run)
```

`aq_sampladata_by_county`

aq_sampladata_by_county

Description

[Stable] Returns a single tibble with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQSAPI_v2` object returned from each successive call to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter, stateFIPS and county_code provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call `/(useful for debugging/)`. This function returns `NULL` is `bdate > edate`.

Usage

```
aqs_sampledata_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  duration = NA_character_,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. Use aqs_sampledurations() for a list of all available duration codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors matching stateFIPS and county_code for the given parameter. An AQS_DataMart_APIv2 is a 2 item named list in which the first item *//(\$Header/)* is a tibble of header information from the AQS API and the second item *//(\$Data/)* is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aq_sannualsummary_by_county\(\)](#), [aq_sdailysummary_by_county\(\)](#), [aq_smonitors_by_county\(\)](#), [aq_sqa_annualperformanceeval_by_county\(\)](#), [aq_sqa_blanks_by_county\(\)](#), [aq_sqa_collocated_assessments_by_county\(\)](#), [aq_sqa_flowrateaudit_by_county\(\)](#), [aq_sqa_flowrateverification_by_county\(\)](#), [aq_sqa_one_point_qc_by_county\(\)](#), [aq_sqa_pep_audit_by_county\(\)](#), [aq_squarterlysummary_by_county\(\)](#), [aq_squarterlysummary_by_site\(\)](#), [aq_stransactionsample_by_county\(\)](#)

Examples

```
# returns all FRM/FEM PM2.5 data for Wake County, NC between
#   January 1, 2015 - February 28, 2016
## Not run: aq_ssampledata_by_county(parameter = '88101',
                                   bdate = as.Date('20150101',
                                                    format = '%Y%m%d'),
                                   edate=as.Date('20160228',
                                                  format = '%Y%m%d'),
                                   stateFIPS = '37',
                                   countycode = '183'
                                   )

## End(Not run)
```

aq_ssampledata_by_site

aq_ssampledata_by_site

Description

[Stable] Returns multiple years of data where sample data is aggregated at the site level. If `return_header` is `FALSE` (default) returns a single data frame with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQS-API_v2` object returned from each successive calls to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter, `stateFIPS` and `county_code` provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call (useful for debugging). Returns `NULL` is `bdate > edate`.

Usage

```
aqs_sampledata_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  duration = NA_character_,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
<code>stateFIPS</code>	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
<code>countycode</code>	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
<code>sitenum</code>	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
<code>duration</code>	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of <code>NA_character_</code> results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or <code>\$O_3\$</code>

	rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. Use aq_ssampledurations() for a list of all available duration codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for a single site with the input parameter. An AQS_DataMart_APIv2 is a 2 item named list in which the first item */(\$Header/)* is a tibble of header information from the AQS API and the second item */(\$Data/)* is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_sannualsummary_by_site\(\)](#), [aq_sdailysummary_by_site\(\)](#), [aq_smonitors_by_site\(\)](#), [aq_sqa_annualperformanceeval_by_site\(\)](#), [aq_sqa_annualperformanceevaltransaction_by_site\(\)](#), [aq_sqa_blanks_by_site\(\)](#), [aq_sqa_collocated_assessment_by_site\(\)](#), [aq_sqa_flowrateaudit_by_site\(\)](#), [aq_sqa_flowrateverification_by_site\(\)](#), [aq_sqa_one_point_qc_by_site\(\)](#), [aq_sqa_pep_audit_by_site\(\)](#), [aq_stransactionsample_by_site\(\)](#)

Examples

```
#Returns a table of ozone monitoring data for the Millbrook School
# site (/#0014) in Wake County, NC for June 18, 2017.
## Not run:
  aq_ssampledata_by_site(parameter = '44201',
                        bdate = as.Date('20170618',
                                         format = '%Y%m%d'),
                        edate = as.Date('20190618',
```

```

                                format = '%Y%m%d'),
                                stateFIPS = '37',
                                countycode = '183',
                                sitenum = '0014'
                                )

## End(Not run)

```

aqs_sampledata_by_state

aqs_sampledata_by_state

Description

[Stable] Returns sample data where the data is aggregated at the state level. If return_header is FALSE (default) this function returns a single dataframe with the requested data. If return_header is TRUE returns a list of AQSAPI_v2 objects where each index of the list is an individual RAQS-API_v2 object returned from each successive call to the AQS API. RAQSAPI_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter and stateFIPS provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call /(useful for debugging/). This function returns NULL is bdate > edate.

Usage

```

aqs_sampledata_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  duration = NA_character_,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.


```

                                format='%Y%m%d'
                                ),
    edate = as.Date('19990515',
                    format = '%Y%m%d'),
    stateFIPS = '37'
  )

## End(Not run)

```

aq_sampl durations	<i>aq_sampl durations</i>
--------------------	---------------------------

Description

[Stable] Returns a table of sample durations and their associated duration codes. Returned values are not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages.

Usage

```
aq_sampl durations(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of sample durations and their associated duration codes (groups of parameters, i.e. 'criteria' or 'all').

Note

Not all sample durations that are available through AQS are available through the AQS Data Mart API, including certain calculated sample durations. Only sample durations that are available through the AQS Data Mart API are returned.

Examples

```

# Returns a tibble or an AQS_DataMart_APIv2 S3 object of
## Not run: aq_sampl durations()

```

aqs_sign_up

aqs_sign_up

Description

[Stable] Use this function to register as a new user or to reset an existing user's key. A verification email will be sent to the email account specified. To reset a password: If the request is made with an email that is already registered, a new key will be issued for that account and emailed to the listed address. Usage is the same in either case. Refer to the email message for further instructions before continuing.

Usage

```
aqs_sign_up(email)
```

Arguments

email	a R character object which represents the email account that will be used to register with the AQS API or change an existing user's key. A verification email will be sent to the account specified. Follow the instructions in the verification e-mail before proceeding to use any other functionality of the AQS API. Register your credential with aqs_credentials() before using the other functions in this library.
-------	--

Value

NULL, This functions is called for its side effect and does not return meaningful data.

Examples

```
# to register a new user or generate a new key with the email
# address 'John.Doe@myemail.com'
## Not run: aqs_sign_up(email = 'John.Doe@myemail.com')
# after calling this function please follow the instructions that
# are sent in the verification e-mail before proceeding.
```

aqs_sites_by_county

aqs_sites_by_county

Description

[Stable] Returns data containing a table of all air monitoring sites with the input state and county FIPS code combination.

Usage

```
aqs_sites_by_county(stateFIPS, countycode, return_header = FALSE)
```

Arguments

- stateFIPS a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use `aqstates()` for the list of available FIPS codes.
- countycode a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use `aqcounties_by_state()` for the list of available county codes in each state.
- return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of all air monitoring sites with the requested state and county FIPS codes.

Examples

```
# Returns an AQS_DataMart_APIv2 S3 object witch returns all sites
# in Hawaii County, HI
## Not run: aqs_sites_by_county(stateFIPS = '15',
                             countycode = '001')

## End(Not run)
```

aqstates	<i>aqstates</i>
----------	-----------------

Description

[Stable] Returns a table of US states, US territories, and the district or Columbia with their respective FIPS codes.

Usage

```
aqstates(return_header = FALSE)
```

Arguments

- return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of states and their associated FIPS codes.

Examples

```
# Returns a tibble of states and their FIPS codes
## Not run: aqs_states()
```

```
aq_transactionsample_by_county
      aq_transactionsample_by_county
```

Description

[Stable] Returns transactionsample data - aggregated by county in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, stateFIPS and countycode provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aq_transactionsample_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aq_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aq_counties_by_state() for the list of available county codes in each state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

```
aqs_transactionsample_by_MA
      aqs_transactionsample_MA
```

Description

[Stable] Returns transactionsample data - aggregated by Monitoring agency (MA) in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes). Use aqs_mas() for a list of all Monitoring Agency (MA) codes and names available,
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_state functions: [aqsq_a_annualperformanceeval_by_state\(\)](#), [aqsq_a_annualperformanceeval_by_state\(\)](#), [aqsq_q_quarterlysummary_by_box\(\)](#), [aqsq_q_quarterlysummary_by_cbsa\(\)](#), [aqsq_q_quarterlysummary_by_state\(\)](#), [aq_transactionsample_by_state\(\)](#)

Examples

```
#Returns a tibble of ozone transaction sample data for all monitors
#operated by South Coast Air Quality Management District collected
#on May 15, 2015
## Not run: aqs_transactionsample_by_MA(parameter = '44201',
                                         bdate = as.Date('20150515',
                                                         format = '%Y%m%d'),
                                         edate = as.Date('20150515',
                                                         format = '%Y%m%d'),
                                         MA_code = '0972'
                                         )

## End(Not run)
```

aq_transactionsample_by_site

aq_transactionsample_by_site

Description

[Stable] Returns transactionsample data aggregated by site in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). Use aqs_counties_by_state() for the list of available county codes in each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested. Use aqs_sites_by_county() for the list of available site numbers in given county and state.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_site functions: [aq_annualsummary_by_site\(\)](#), [aq_dailysummary_by_site\(\)](#), [aq_monitors_by_site\(\)](#), [aq_qa_annualperformanceeval_by_site\(\)](#), [aq_qa_annualperformanceevaltransaction_by_site\(\)](#), [aq_qa_blanks_by_site\(\)](#), [aq_qa_collocated_assessment_by_site\(\)](#), [aq_qa_flowrateaudit_by_site\(\)](#), [aq_qa_flowrateverification_by_site\(\)](#), [aq_qa_one_point_qc_by_site\(\)](#), [aq_qa_pep_audit_by_site\(\)](#), [aq_sampledata_by_site\(\)](#)

Examples

```
#Returns a AQS_DataMart_APIv2 S3 object of the returns
## Not run: # returns all ozone transaction data for the
# Millbrook School site (#0014) in Wake County, NC for
# June 18, 2017
aq_transactionsample_by_site(parameter = '44201',
                             bdate = as.Date('20170618',
                                                format = '%Y%m%d'),
                             edate = as.Date('20170618',
                                                format = '%Y%m%d'),
                             stateFIPS = '37',
                             countycode = '183',
                             sitenum = '0014'
                             )

## End(Not run)
```

```
aq_transactionsample_by_state
aq_transactionsample_by_state
```

Description

[Stable] Returns transactionsample data - aggregated by state in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = lubridate::NA_Date_,
  cedate = lubridate::NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents the begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents the end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. Use aqs_states() for the list of available FIPS codes.
cbdate	a R date object which represents a 'beginning date of last change' that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an 'end date of last change' that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server, mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_DataMart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that

it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $\mathcal{O}(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_state functions: [aqst_qa_annualperformanceeval_by_state\(\)](#), [aqst_qa_annualperformanceeval_by_box\(\)](#), [aqst_quarterlysummary_by_box\(\)](#), [aqst_quarterlysummary_by_cbsa\(\)](#), [aqst_quarterlysummary_by_state\(\)](#), [aqst_transactionsample_by_MA\(\)](#)

Examples

```
#Returns a AQS_DataMart_APIv2 S3 object of
## Not run: # Returns a tibble containing benzene transaction sample
# data for North Carolina on May 15, 1995
aqst_transactionsample_by_state(parameter = '45201',
                                bdate = as.Date('19950515',
                                                  format = '%Y%m%d'),
                                edate = as.Date('19950515',
                                                  format = '%Y%m%d'),
                                stateFIPS = '37'
                                )

## End(Not run)
```

Index

* **Aggregate_by_MA functions**

aqs_qa_annualperformanceeval_by_MA, [39](#)
aqs_qa_annualperformanceevaltransaction_by_MA, [47](#)
aqs_qa_blanks_by_MA, [56](#)
aqs_qa_collocated_assessments_by_MA, [64](#)
aqs_qa_flowrateaudit_by_MA, [72](#)
aqs_qa_flowrateverification_by_MA, [80](#)
aqs_qa_one_point_qc_by_MA, [88](#)
aqs_qa_pep_audit_by_MA, [96](#)

* **Aggregate_by_box functions**

aqs_annualsummary_by_box, [4](#)
aqs_monitors_by_box, [29](#)
aqs_sampledata_by_box, [114](#)

* **Aggregate_by_cbsa functions**

aqs_annualsummary_by_cbsa, [6](#)
aqs_dailysummary_by_cbsa, [19](#)
aqs_monitors_by_cbsa, [30](#)
aqs_sampledata_by_cbsa, [116](#)

* **Aggregate_by_county functions**

aqs_annualsummary_by_county, [8](#)
aqs_dailysummary_by_county, [21](#)
aqs_monitors_by_county, [32](#)
aqs_qa_annualperformanceeval_by_county, [37](#)
aqs_qa_blanks_by_county, [54](#)
aqs_qa_collocated_assessments_by_county, [62](#)
aqs_qa_flowrateaudit_by_county, [70](#)
aqs_qa_flowrateverification_by_county, [78](#)
aqs_qa_one_point_qc_by_county, [87](#)
aqs_qa_pep_audit_by_county, [95](#)
aqs_quarterlysummary_by_county, [107](#)
aqs_quarterlysummary_by_site, [109](#)

aqs_sampledata_by_county, [118](#)

aqs_transactionsample_by_county, [128](#)

* **Aggregate_by_pqao functions**

aqs_qa_annualperformanceeval_by_pqao, [41](#)
aqs_qa_annualperformanceevaltransaction_by_pqao, [49](#)
aqs_qa_blanks_by_pqao, [57](#)
aqs_qa_collocated_assessments_by_pqao, [65](#)
aqs_qa_flowrateaudit_by_pqao, [73](#)
aqs_qa_flowrateverification_by_pqao, [82](#)
aqs_qa_one_point_qc_by_pqao, [90](#)
aqs_qa_pep_audit_by_pqao, [98](#)

* **Aggregate_by_site functions**

aqs_annualsummary_by_site, [10](#)
aqs_dailysummary_by_site, [23](#)
aqs_monitors_by_site, [33](#)
aqs_qa_annualperformanceeval_by_site, [42](#)
aqs_qa_annualperformanceevaltransaction_by_county, [46](#)
aqs_qa_annualperformanceevaltransaction_by_site, [51](#)
aqs_qa_blanks_by_site, [59](#)
aqs_qa_collocated_assessments_by_site, [67](#)
aqs_qa_flowrateaudit_by_site, [75](#)
aqs_qa_flowrateverification_by_site, [83](#)
aqs_qa_one_point_qc_by_site, [91](#)
aqs_qa_pep_audit_by_site, [99](#)
aqs_sampledata_by_site, [120](#)
aqs_transactionsample_by_site, [131](#)

* **Aggregate_by_state functions**

aqs_qa_annualperformanceeval_by_state, [44](#)

- aqs_qa_annualperformanceevaltransaction_by_state, 52
- aqs_quarterlysummary_by_box, 103
- aqs_quarterlysummary_by_cbsa, 105
- aqs_quarterlysummary_by_state, 111
- aqs_transactionsample_by_MA, 130
- aqs_transactionsample_by_state, 133
- * **Aggregate_by_box functions**
 - aqs_dailysummary_by_box, 17
- * **Aggregate_by_state functions**
 - aqs_annualsummary_by_state, 12
 - aqs_dailysummary_by_state, 25
 - aqs_monitors_by_state, 35
 - aqs_qa_blanks_by_state, 60
 - aqs_qa_collocated_assessments_by_state, 69
 - aqs_qa_flowrateaudit_by_state, 77
 - aqs_qa_flowrateverification_by_state, 85
 - aqs_qa_one_point_qc_by_state, 93
 - aqs_qa_pep_audit_by_state, 101
 - aqs_sampledata_by_state, 123
- aqs_annualsummary_by_box, 4
- aqs_annualsummary_by_box(), 30, 116
- aqs_annualsummary_by_cbsa, 6
- aqs_annualsummary_by_cbsa(), 20, 31, 118
- aqs_annualsummary_by_county, 8
- aqs_annualsummary_by_county(), 22, 33, 39, 55, 63, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_annualsummary_by_site, 10
- aqs_annualsummary_by_site(), 24, 34, 44, 47, 52, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_annualsummary_by_state, 12
- aqs_annualsummary_by_state(), 26, 36, 62, 70, 78, 86, 94, 102, 124
- aqs_cbsas, 14
- aqs_cbsas(), 7, 19, 31, 105, 117
- aqs_classes, 15
- aqs_classes(), 36
- aqs_counties_by_state, 15
- aqs_counties_by_state(), 9, 11, 21, 23, 32, 34, 38, 43, 46, 51, 55, 59, 63, 67, 71, 76, 79, 84, 87, 92, 95, 100, 107, 109, 119, 121, 127, 128, 132
- aqs_credentials, 16
- aqs_credentials(), 126
- aqs_dailysummary_by_box, 17
- aqs_dailysummary_by_cbsa, 19
- aqs_dailysummary_by_cbsa(), 8, 31, 118
- aqs_dailysummary_by_county, 21
- aqs_dailysummary_by_county(), 10, 33, 39, 55, 63, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_dailysummary_by_site, 23
- aqs_dailysummary_by_site(), 12, 34, 44, 47, 52, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_dailysummary_by_state, 25
- aqs_dailysummary_by_state(), 14, 36, 62, 70, 78, 86, 94, 102, 124
- aqs_fields_by_service, 26
- aqs_isavailable, 27
- aqs_knownissues, 28
- aqs_mas, 28
- aqs_mas(), 40, 48, 56, 64, 72, 80, 89, 97, 130
- aqs_monitors_by_box, 29
- aqs_monitors_by_box(), 6, 116
- aqs_monitors_by_cbsa, 30
- aqs_monitors_by_cbsa(), 8, 20, 118
- aqs_monitors_by_county, 32
- aqs_monitors_by_county(), 10, 22, 39, 55, 63, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_monitors_by_site, 33
- aqs_monitors_by_site(), 12, 24, 44, 47, 52, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_monitors_by_state, 35
- aqs_monitors_by_state(), 14, 26, 62, 70, 78, 86, 94, 102, 124
- aqs_parameters_by_class, 36
- aqs_pqaos, 37
- aqs_pqaos(), 41, 50, 58, 66, 74, 82, 90, 98
- aqs_qa_annualperformanceeval_by_county, 37
- aqs_qa_annualperformanceeval_by_county(), 10, 22, 33, 55, 63, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_qa_annualperformanceeval_by_MA, 39
- aqs_qa_annualperformanceeval_by_MA(), 48, 57, 65, 73, 81, 89, 97
- aqs_qa_annualperformanceeval_by_pqao, 41
- aqs_qa_annualperformanceeval_by_pqao(), 50, 58, 66, 74, 83, 91, 99

- aqs_qa_annualperformanceeval_by_site, 42
- aqs_qa_annualperformanceeval_by_site(), 12, 24, 34, 47, 52, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_qa_annualperformanceeval_by_state, 44
- aqs_qa_annualperformanceeval_by_state(), 54, 104, 106, 112, 131, 135
- aqs_qa_annualperformanceevaltransaction_by_county, 46
- aqs_qa_annualperformanceevaltransaction_by_county(), 12, 24, 34, 44, 52, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_qa_annualperformanceevaltransaction_by_MA, 47
- aqs_qa_annualperformanceevaltransaction_by_MA(), 40, 57, 65, 73, 81, 89, 97
- aqs_qa_annualperformanceevaltransaction_by_pqao, 49
- aqs_qa_annualperformanceevaltransaction_by_pqao(), 42, 58, 66, 74, 83, 91, 99
- aqs_qa_annualperformanceevaltransaction_by_site, 51
- aqs_qa_annualperformanceevaltransaction_by_site(), 12, 24, 34, 44, 47, 60, 68, 76, 85, 93, 101, 122, 133
- aqs_qa_annualperformanceevaltransaction_by_state, 52
- aqs_qa_annualperformanceevaltransaction_by_state(), 45, 104, 106, 112, 131, 135
- aqs_qa_blanks_by_county, 54
- aqs_qa_blanks_by_county(), 10, 22, 33, 39, 63, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_qa_blanks_by_MA, 56
- aqs_qa_blanks_by_MA(), 40, 48, 65, 73, 81, 89, 97
- aqs_qa_blanks_by_pqao, 57
- aqs_qa_blanks_by_pqao(), 42, 50, 66, 74, 83, 91, 99
- aqs_qa_blanks_by_site, 59
- aqs_qa_blanks_by_site(), 12, 24, 34, 44, 47, 52, 68, 76, 85, 93, 101, 122, 133
- aqs_qa_blanks_by_state, 60
- aqs_qa_blanks_by_state(), 14, 26, 36, 70, 78, 86, 94, 102, 124
- aqs_qa_collocated_assessments_by_county, 62
- aqs_qa_collocated_assessments_by_county(), 10, 22, 33, 39, 55, 71, 79, 88, 96, 108, 110, 120, 129
- aqs_qa_collocated_assessments_by_MA, 64
- aqs_qa_collocated_assessments_by_MA(), 40, 48, 57, 73, 81, 89, 97
- aqs_qa_collocated_assessments_by_pqao, 65
- aqs_qa_collocated_assessments_by_pqao(), 42, 50, 58, 74, 83, 91, 99
- aqs_qa_collocated_assessments_by_site, 67
- aqs_qa_collocated_assessments_by_site(), 12, 24, 34, 44, 47, 52, 60, 76, 85, 93, 101, 122, 133
- aqs_qa_collocated_assessments_by_state, 69
- aqs_qa_collocated_assessments_by_state(), 14, 26, 36, 62, 78, 86, 94, 102, 124
- aqs_qa_flowrateaudit_by_county, 70
- aqs_qa_flowrateaudit_by_county(), 10, 22, 33, 39, 55, 63, 79, 88, 96, 108, 110, 120, 129
- aqs_qa_flowrateaudit_by_MA, 72
- aqs_qa_flowrateaudit_by_MA(), 40, 48, 57, 65, 81, 89, 97
- aqs_qa_flowrateaudit_by_pqao, 73
- aqs_qa_flowrateaudit_by_pqao(), 42, 50, 58, 66, 83, 91, 99
- aqs_qa_flowrateaudit_by_site, 75
- aqs_qa_flowrateaudit_by_site(), 12, 24, 34, 44, 47, 52, 60, 68, 85, 93, 101, 122, 133
- aqs_qa_flowrateaudit_by_state, 77
- aqs_qa_flowrateaudit_by_state(), 14, 26, 36, 62, 70, 86, 94, 102, 124
- aqs_qa_flowrateverification_by_county, 78
- aqs_qa_flowrateverification_by_county(), 10, 22, 33, 39, 55, 63, 71, 88, 96, 108, 110, 120, 129
- aqs_qa_flowrateverification_by_MA, 80
- aqs_qa_flowrateverification_by_MA(), 40, 48, 57, 65, 73, 89, 97
- aqs_qa_flowrateverification_by_pqao, 82
- aqs_qa_flowrateverification_by_pqao(),

- [42, 50, 58, 66, 74, 91, 99](#)
- [aqs_qa_flowrateverification_by_site,](#)
[83](#)
- [aqs_qa_flowrateverification_by_site\(\),](#)
[12, 24, 34, 44, 47, 52, 60, 68, 76, 93,](#)
[101, 122, 133](#)
- [aqs_qa_flowrateverification_by_state,](#)
[85](#)
- [aqs_qa_flowrateverification_by_state\(\),](#)
[14, 26, 36, 62, 70, 78, 94, 102, 124](#)
- [aqs_qa_one_point_qc_by_county,](#) [87](#)
- [aqs_qa_one_point_qc_by_county\(\),](#) [10, 22,](#)
[33, 39, 55, 63, 71, 79, 96, 108, 110,](#)
[120, 129](#)
- [aqs_qa_one_point_qc_by_MA,](#) [88](#)
- [aqs_qa_one_point_qc_by_MA\(\),](#) [40, 49, 57,](#)
[65, 73, 81, 97](#)
- [aqs_qa_one_point_qc_by_pqao,](#) [90](#)
- [aqs_qa_one_point_qc_by_pqao\(\),](#) [42, 50,](#)
[58, 66, 74, 83, 99](#)
- [aqs_qa_one_point_qc_by_site,](#) [91](#)
- [aqs_qa_one_point_qc_by_site\(\),](#) [12, 24,](#)
[34, 44, 47, 52, 60, 68, 76, 85, 101,](#)
[122, 133](#)
- [aqs_qa_one_point_qc_by_state,](#) [93](#)
- [aqs_qa_one_point_qc_by_state\(\),](#) [14, 26,](#)
[36, 62, 70, 78, 86, 102, 124](#)
- [aqs_qa_pep_audit_by_county,](#) [95](#)
- [aqs_qa_pep_audit_by_county\(\),](#) [10, 22, 33,](#)
[39, 55, 63, 71, 79, 88, 108, 110, 120,](#)
[129](#)
- [aqs_qa_pep_audit_by_MA,](#) [96](#)
- [aqs_qa_pep_audit_by_MA\(\),](#) [40, 49, 57, 65,](#)
[73, 81, 89](#)
- [aqs_qa_pep_audit_by_pqao,](#) [98](#)
- [aqs_qa_pep_audit_by_pqao\(\),](#) [42, 50, 58,](#)
[66, 74, 83, 91](#)
- [aqs_qa_pep_audit_by_site,](#) [99](#)
- [aqs_qa_pep_audit_by_site\(\),](#) [12, 24, 34,](#)
[44, 47, 52, 60, 68, 76, 85, 93, 122,](#)
[133](#)
- [aqs_qa_pep_audit_by_state,](#) [101](#)
- [aqs_qa_pep_audit_by_state\(\),](#) [14, 26, 36,](#)
[62, 70, 78, 86, 94, 124](#)
- [aqs_quarterlysummary_by_box,](#) [103](#)
- [aqs_quarterlysummary_by_box\(\),](#) [45, 54,](#)
[106, 112, 131, 135](#)
- [aqs_quarterlysummary_by_cbsa,](#) [105](#)
- [aqs_quarterlysummary_by_cbsa\(\),](#) [45, 54,](#)
[104, 112, 131, 135](#)
- [aqs_quarterlysummary_by_county,](#) [107](#)
- [aqs_quarterlysummary_by_county\(\),](#) [10,](#)
[22, 33, 39, 55, 63, 71, 79, 88, 96,](#)
[110, 120, 129](#)
- [aqs_quarterlysummary_by_site,](#) [109](#)
- [aqs_quarterlysummary_by_site\(\),](#) [10, 22,](#)
[33, 39, 55, 63, 71, 79, 88, 96, 108,](#)
[120, 129](#)
- [aqs_quarterlysummary_by_state,](#) [111](#)
- [aqs_quarterlysummary_by_state\(\),](#) [45, 54,](#)
[104, 106, 131, 135](#)
- [aqs_removeheader,](#) [113](#)
- [aqs_revisionhistory,](#) [113](#)
- [aqs_sampledata_by_box,](#) [114](#)
- [aqs_sampledata_by_box\(\),](#) [6, 30](#)
- [aqs_sampledata_by_cbsa,](#) [116](#)
- [aqs_sampledata_by_cbsa\(\),](#) [8, 20, 31](#)
- [aqs_sampledata_by_county,](#) [118](#)
- [aqs_sampledata_by_county\(\),](#) [10, 22, 33,](#)
[39, 55, 63, 71, 79, 88, 96, 108, 110,](#)
[129](#)
- [aqs_sampledata_by_site,](#) [120](#)
- [aqs_sampledata_by_site\(\),](#) [12, 24, 34, 44,](#)
[47, 52, 60, 68, 76, 85, 93, 101, 133](#)
- [aqs_sampledata_by_state,](#) [123](#)
- [aqs_sampledata_by_state\(\),](#) [14, 26, 36, 62,](#)
[70, 78, 86, 94, 102](#)
- [aqs_sampledurations,](#) [125](#)
- [aqs_sampledurations\(\),](#) [115, 117, 119, 122,](#)
[124](#)
- [aqs_sign_up,](#) [126](#)
- [aqs_sign_up\(\),](#) [16](#)
- [aqs_sites_by_county,](#) [126](#)
- [aqs_sites_by_county\(\),](#) [11, 23, 34, 43, 51,](#)
[59, 67, 76, 84, 92, 100, 109, 121, 132](#)
- [aqs_states,](#) [127](#)
- [aqs_states\(\),](#) [9, 11, 13, 16, 21, 23, 25, 32,](#)
[34, 35, 38, 43, 45, 46, 51, 53, 55, 59,](#)
[61, 63, 67, 69, 71, 75, 77, 79, 84, 86,](#)
[87, 92, 94, 95, 100, 102, 107, 109,](#)
[111, 119, 121, 123, 127, 128, 132,](#)
[134](#)
- [aqs_transactionsample_by_county,](#) [128](#)
- [aqs_transactionsample_by_county\(\),](#) [10,](#)
[22, 33, 39, 55, 63, 71, 79, 88, 96,](#)
[108, 110, 120](#)

`aqs_transactionsample_by_MA`, 130
`aqs_transactionsample_by_MA()`, 45, 54,
104, 106, 112, 135
`aqs_transactionsample_by_site`, 131
`aqs_transactionsample_by_site()`, 12, 24,
34, 44, 47, 52, 60, 68, 76, 85, 93,
101, 122
`aqs_transactionsample_by_state`, 133
`aqs_transactionsample_by_state()`, 45,
54, 104, 106, 112, 131